

INDEX

- A**
- Absolute bandwidth, 72
 - Accept policy, TCP, 681
 - Access control, WPA, 738–739
 - Access point (AP), 802.11 model, 532
 - Acknowledge policy, TCP, 682
 - Acknowledged connectionless service, LLC, 460, 461
 - Acknowledgement (ACK), 58, 215, 216, 218, 219, 540, 542, 677, 679
 - frame, 215
 - IEEE 802.11 MAC, 540, 542
 - negative, 216
 - number, TCP, 677, 679
 - packet, 58
 - positive, 216
 - receive ready (RR), 218, 219
 - reject (REQ), 218, 219
 - Active attacks, 702, 704–705. *See also* Message authentication
 - Ad hoc networking, 526
 - Adaptation layer (AAL), ATM, 330
 - Adaptive equalization, 426–427
 - Adaptive routing, 360–362
 - Additional records section, DNS messages, 783, 784
 - Address field, 224, 323, 579–582, 590–591
 - destination, IP, 597, 591
 - dotted decimal notation, 580
 - extension (EA), frame relay, 323
 - flow label, IPv6, 590, 591–592
 - HDLC, 224
 - Internet Protocol (IP), 579–582
 - IPv6, 590–591
 - network classes, IP, 579–580
 - source, IP, 579, 590
 - subnets and subnet masks, 580–582
 - Address mask request/reply message, ICMP, 585
 - Address Resolution Protocol (ARP), 585–586
 - Addresses, 25, 37, 38, 541, 558
 - IEEE 802.11 MAC, 541
 - IP, 25
 - PDU control information, 558
 - subnetwork, 38
 - TCP, 37
 - Addressing, 18, 45, 208, 562–564, 657–658
 - anycast, 593
 - broadcast, 564
 - connection identifiers, 564
 - data link control protocol, 208
 - defined, 18
 - global applicability, 563
 - global nonambiguity, 563
 - Host, 653
 - IPv6, 592–593
 - level, 563
 - mode, 564
 - multicast, 564, 593
 - network service, 657–658
 - OSI model, 45
 - Port, 653
 - protocol function, 562–564
 - scope, 563
 - socket, 658
 - unicast, 564, 592
 - Admission control, ISA, 629, 630
 - ADSL, *see* Asymmetrical digital subscriber line (ADSL)
 - Advanced Encryption Standard (AES), 707–710
 - Advanced Mobile Phone Service (AMPS), 427–429
 - control channels, 428–429
 - operation, 428
 - reverse control channels (RCCs), 428–429
 - spectral allocation, 427–428
 - Aggregate peak demand, VPC, 401–402
 - Aggregator field, BGP, 620–621
 - Alert Protocol, 730
 - Algorithms, 362–367, 367–372, 470, 472–473, 486, 550, 629, 686–688, 689–690, 705–710, 718–720, 723–726, 803–805
 - Advanced Encryption Standard (AES), 707–710
 - ARAPNET, 362–367
 - Bellman-Ford, 370–371, 371–372
 - Data Encryption Standard (DES), 707
 - decryption, 706
 - Dijkstra's, 368–370, 371–372
 - encryption, 705, 707–710, 723–726
 - Jacobson's, 686–688
 - Karn's, 689–690
 - least-cost, 367–372
 - MPEG video compression, 803–805
 - nonpersistent CSMA, 486
 - routing, 362–367, 367–372, 629
 - RSA public-key encryption, 723–726
 - Secure Hash, 718–720
 - spanning tree, 470, 472–473
 - Wired Equivalent Privacy (WEP), 550
 - ALOHA, 485
 - Alternate mark inversion (AMI)
 - coding, 268
 - Amplitude modulation (AM), 169–171
 - Amplitude shift keying (ASK), 139, 151–152
 - AMPS, *see* Advanced Mobile Phone Service (AMPS)
 - Analog, 66, 67, 78–86, 139, 140–141, 151–161, 162–168, 168–175, 246–247, 427–429. *See also* Encoding
 - audio data, 78, 81–82
 - carrier systems, FDM, 246–247
 - cellular wireless networks, 427–429
 - clarification of term, 66, 78
 - data, 78–86, 140–141, 162–168, 168–175
 - encoding, data and signal combinations, 139, 140–141, 151–161, 162–168, 168–175
 - integration with digital data, 86
 - signal, 67, 80–86, 140–141, 151–161, 168–175
 - signaling, 139
 - transmission, 84–85
 - video data, 78–79, 82
 - Anchor frame, video compression, 805
 - Angle modulation, 171–174
 - Answer section, DNS messages, 783, 784
 - Antennas, 117–119, 119–120, 125–129, 129–133
 - atmospheric absorption, 132
 - defined, 117
 - effective area, 118
 - free space loss, 129–132
 - gain, 118–119
 - ground wave propagation, 125
 - isotropic, 117
 - line of sight (LOS), 125–129, 129–133
 - parabolic reflective, 117–118
 - sky wave propagation, 125
 - terrestrial microwave, 119–120
 - wireless propagation of, 125–129
 - wireless transmission by, 113–119
 - Anycast addresses, 593
 - Aperiodic signal, 68, 837, 839–840
 - bandwidths, 837, 839–840
 - defined, 68
 - Fourier transform representation of, 837, 839–840
 - power spectral density (PSD), 837, 839–840
 - Application layer, TCP/IP, 36
 - Application-defined packet, RTPC, 828, 831
 - ARAPNET, 362–367
 - delay metrics, 366–367
 - first generation routing algorithm, 362–364
 - second generation routing algorithm, 364
 - third generation routing algorithm, 364–367
 - Architecture, 25–29, 32–61, 321–322, 329–330, 457–465, 466, 468, 503, 531–533, 604, 625–636, 636–645, 728, 762–764, 821–822
 - application-level framing, 821–822
 - ATM protocol, 329–330
 - bridge protocol, LAN, 466, 468
 - Differentiated Services (DS), 604, 636–645
 - Fibre Channel protocol, 503
 - frame relay protocol, 321–322
 - IEEE 802.11, 531–533
 - integrated layer processing, 822
 - Integrated Services (ISA), 604, 625–636
 - Internet, 25–29
 - LAN protocol, 457–465
 - multimedia, 48–53
 - Open Systems Interconnection (OSI) model, 42–44
 - protocol, 32–61
 - RTP protocol, 821–822
 - Secure Socket Layer (SSL), 728
 - Simple Network Management Protocol (SNMP), 762–764
 - TCP/IP protocol, 34–42
 - Wireless Fidelity (Wi-Fi) Alliance, 532
 - wireless LANs (WLAN), 531–533
 - ARQ, *see* Automatic repeat request (ARQ)

- AS, *see* Autonomous system (AS)
- AS_Path attribute, BGP, 620, 621, 622
- Association-related services, 802.11
model, 535
- Assured forwarding (AF) PFB, 644–645
- Asymmetric, defined, 265
- Asymmetrical digital subscriber line (ADSL), 265–268
design, 265–267
discrete multitone (DMT), 267–268
quadrature amplitude modulation (QAM), 267
- Asynchronous balanced mode (ABM), 222
- Asynchronous response mode (ARM), 222
- Asynchronous transfer mode (ATM), 8, 23–24, 296, 328–350, 394–406, 406–408
adaptation layer (AAL), 330
cell-based physical layer, 340–343
cell delay variation (CDV), 395–398, 402–403
cells, 330, 335–340, 340–345
congestion control, 394–406, 406–408
connection admission control, 402–404
constant bit-rate (CBR), 402–403
control plane, 330
Forum, 8
Generic Flow Control (GFC), 336, 338–339
guaranteed frame rate (GFR), 406–408
Header Error Control (HEC), 338, 339–340
introduction to, 296, 329
latency/speed effects, traffic control, 395
logical connections, 331–335
management plane, 330
non-real-time service, 345, 346–348
peak cell rate (PCR), 402–403
protocol architecture, 329–330
real-time service, 345–346
recommended reading and Web sites, 348–349
resource management, 400–402
SDH-based physical layer, 343–345
selective cell discard, 405
services, 345–348
sustainable cell rate (SCR), 402–403
Synchronous Digital Hierarchy (SDH), 329, 343–345
traffic management, 394–406
traffic shaping, 405–406
transmission of cells, 340–345
usage parameter control (UPC), 404–405
use of, 23–24
user plane, 330
variable-bit rate (VBR), 402–403
virtual paths, 400–402
- Asynchronous transmission, 181, 182–185
defined, 181
framing error, 184
idle state, 183
stop element, 183
- ATM, *see* Asynchronous transfer mode (ATM)
- Atmospheric absorption, 132
- Atomic_Aggregate field, BGP, 620–621
- Attacks, 702, 704–705, 706
active, 702, 704–705
brute-force, 706
cryptanalysis, 706
passive, 702, 704
- Attenuation, 86–87, 88, 99, 108, 129–133
atmospheric absorption, 132
free space loss, 129–132
guided transmission impairment, 108
intersymbol interference, 87
multipath interference, 132
scattering, 116, 132
signal strength, 99
transmission impairment, 86–87, 88
wireless line-of-sight impairment, 129–133
- Audio, 50, 78, 81–82, 801–802
analog data, 78, 81–82
compression, 801–802
media type, 50
pulse-code modulation (PAM), 801
transmission, 81–82
- Audio type, MIME, 757
- Authentication, 550, 588, 737–738. *See also* Message authentication header, IPv6, 588
IEEE 802.11, 550
WPA, 737–738
- Authentication Header (AH), IPSec, 599, 734–736
- Authenticity, defined, 703
- Authority section, DNS messages, 783, 784
- Automatic repeat request (ARQ), 216–221, 236–238
continuous, 217
damaged frames, 219
error control, 216–221, 236–238
go-back-N, 217–221, 238
performance of, 236–238
receive ready (RR) acknowledgement, 218, 219
reject (REQ) acknowledgement, 218, 219
selective-reject, 221, 237
stop-and-wait, 217, 237
- Autonomous system (AS), 614–616, 623–625
characteristics of, 614–615
exterior router protocol (ERP), 616
interior router protocol (IRP), 615–616
OSPF example of, 623–625
- Aux Data Length, IGMP, 613
- Auxiliary Data field, IGMP, 613
- Availability, defined, 703
- Available bit rate (ABR), 345, 347
- B**
- Backbone LANs, 15, 450–451, 485, 527–528
function of, 450–451
high-speed local, 15, 485
wireless connection to, 527–528
- Backend networks, 448–449
- Backpressure, 384
- Backus-Naur Form (BNF), 788–790
- Backward explicit congestion notification (BECN), 393
- Balanced configuration, HDLQ, 222
- Bandwidth, 72–78, 79, 92–93, 104, 158, 439, 837, 839–840
absolute, 72
aperiodic signals, 837, 839–840
channel capacity, 92–93
data rate and, relationship between, 72–78
defined, 72
effective, 72
efficiency, 158
interlacing, 79
Nyquist, 92–93
3G cellular systems, 439
transmission media and, 104
- Barker sequence, DSSS, 544
- Base station, cellular networks, 415
- Baseband signal, 140
- Base64, transfer encoding, 758–760
- Basic services set (BSS), 532
- Battery power consumption, wireless LANs, 528
- Bellman-Ford algorithm, 370–371, 371–372
- Best-effort service, 347
- BGP, *see* Border Gateway Protocol (BGP)
- Binary data, 82–83
- Binary phase-shift keying (BPSK), 154–155, 277–278, 282–284
FHSS using, 277–278
FSSS using, 282–284
signal encoding scheme, 154–155
- Biphase encoding technique, 147–148
advantages of, 147–148
differential Manchester, 147
digital data, digital signal encoding, 147–148
Manchester code, 147
- Bipolar-AMI scheme, 146
- Bipolar with 8-zeros substitution (B8ZS), 150
- Bit error rate (BER), 142
- Bit length, data link, 211
- Block code principles, 197–201
code rate, 199
coding gain, 200–201
design of, 200
Hamming distance, 197
redundancy, 199
- Block-coding methods, 511
- Border Gateway Protocol (BGP), 618–623
functions, 618–619
internetwork routing, 618–623
messages, 619–621
neighbor acquisition, 618
neighbor reachability, 618
Network Layer Reachability Information (NLR1) field, 620, 622
network reachability, 619
Notification Message, 621
Path Attributes field, 620–621
routing information exchange, 621–623
Total Path Attributes Length field, 620
- Bottom-up approach, 3–5
- Bridges, 465–473, 567
address learning, 471–472
fixed routing, 468–471
frame forwarding, 471
functions of, 466, 467
internetworking, 567
LAN use of, 465–473
protocol architecture, 466, 468
spanning tree, 470, 471–473

- Broadcast addressing, 564
 - Broadcast radio, *see* Radio
 - Broadcast storm, 477
 - Broadcast strategy, multicasting, 606–607
 - Buffer management, GFR, 407
 - Bus topology, 447, 451–453, 454
- C**
- Cable, 112, 264–265
 - coaxial, 112
 - modem, 264–265
 - headend, 264
 - Cache, HTTP, 788
 - Call establishment, VCC and VPC, 332
 - Call functions, MTSO, 421–422
 - Call sequence integrity, VCC and VPC, 334
 - Capacity utilization, digital transmission, 86
 - Carrier extension, Gigabit Ethernet, 495
 - Carrier sense multiple access (CSMA), 486–490
 - collision detection, with (CSMA/CD), 483, 488–490
 - nonpersistent CSMA algorithm, 486
 - 1-persistent protocol, 487
 - p*-persistent protocol, 487–488
 - Carrier sense multiple access with collision detection (CSMA/CD), 483, 488–490, 517–518
 - backoff, 488
 - binary exponential backoff, 490
 - description of, 488–490
 - model, high-speed LANs, 517–518
 - operation, 489
 - Carrier signal, 139
 - Carrier systems, 246–247, 253–255
 - analog, 246–247
 - digital, 253–255
 - FDM, 246–247
 - pulse code modulation (PCM), 254
 - signaling bit, 254
 - subcarrier, 243
 - TDM, 253–255
- CDMA, *see* Code division multiple access (CDMA)
- Cell-based physical layer, ATM, 340–343
 - Cell delay variation (CDV), 395–398, 402–403
 - ATM networks, 395–397
 - connection admission control, 402–403
 - UNI, 397–398
 - Cell Loss Priority (CLP) bit, ATM, 337
 - Cell sectoring, cellular capacity, 418
 - Cell splitting, cellular capacity, 417
 - Cells, ATM, 330, 335–340, 340–345, 395–398, 399, 402–403
 - cell-based physical layer, 340–343
 - cell delay variation (CDV), 395–398, 402–403
 - Cell Loss Priority (CLP), 337
 - controlled cell transfer (CCT), ATM, 330
 - defined, 330
 - Generic Flow Control (GFC), 336, 338–339
 - Header Error Control (HEC), 338, 339–340
 - header format, 336–338
 - insertion time, 399
 - Payload Type (PT), 337
 - SDH-based physical layer, 343–345
 - transmission of, 340–345
 - use of, 335
 - Virtual Channel Identifier (VCI), 337
 - Virtual Path Identifier (VPI), 336
 - Cellular wireless networks, 296, 413–443. *See also* Mobile communication
 - Advanced Mobile Phone Service (AMPS), 427–429
 - analog, 427–429
 - base station, 415
 - capacity, 417–419
 - channel access, 429
 - code division multiple access (CDMA), 429–436
 - control channels, 420
 - design considerations, 430–431, 438–440
 - digital traffic channels, 429
 - encryption, 429
 - error detection and correction, 429
 - fading, 424–427
 - first-generation systems, 427–429
 - frequency reuse, 416–417
 - introduction to, 296, 414
 - mobile radio propagation effects, 422–424
 - mobile telecommunications switching office (MTSO), 419–422
 - operation of systems, 419–422
 - organization, 415–419
 - paging, 421, 433
 - principles of, 415–427
 - recommended reading and Web sites, 440–441
 - second generation systems, 429–436
 - third generation (3G) systems, 432–440
 - traffic channels, 420, 429, 433
 - Center frequency, 77
 - Central office (CO), defined, 27, 28
 - Centralized server farms, 14–15
 - Change Cipher Spec Protocol, 730
 - Channel capacity, 91–96
 - bandwidth, 92
 - data rate, 91
 - defined, 91
 - Eb/N0* expression, 94–96
 - error rate, 92
 - noise, 93
 - Nyquist bandwidth, 92–93
 - Shannon formula, 93–94
 - signal-to-noise ratio (SNR), 93–94
 - Channel structure, IEEE 802.11a, 545
 - Channels, 243, 250, 335, 417, 420, 428–429, 432–433. *See also* Fibre Channel
 - access, cellular networks, 429
 - adding new, cellular, 417
 - AMPS, 428–429
 - cellular wireless networks, 417, 420
 - control, 420, 428–429
 - digital traffic, 429
 - FDM, 243
 - IS-95 CDMA, 432–433
 - meta-signaling, 335
 - paging, 433
 - pilot, 433
 - reverse control (RCC), 428–429
 - synchronization, 433
 - TDM, 250
 - traffic, 420, 429, 433
 - user-to-network signaling virtual, 335
 - user-to-user signaling virtual, 335
 - Check bits, 187–188
 - Checksum, 38, 583, 611, 613, 679
 - ICMP, 583
 - IGMP, 611, 613
 - TCP, 38, 679
 - Chip rate, 3G cellular systems, 439
 - Chipping signal, 279
 - Choke packet, 384–385
 - Circuit switching, 23, 295, 298, 301–304, 304–307, 307–309, 315–317
 - concepts, 304–307
 - control unit, 305
 - data transfer, 301
 - defined, 298
 - digital switch, 304–305
 - disconnect, 301
 - establishment, 301, 303
 - media gateway (MG), 308–309
 - media gateway controller (MGC), 308–309
 - network interface, 305
 - networks, 23, 301–304
 - node delay, 315–316
 - packet switching, comparison to, 315–317
 - private branch exchange (PBX), 305
 - propagation delay, 315–316
 - public telecommunications network, 302–303
 - softswitch architecture, 307–309
 - space division switching, 305–307
 - time division switching, 307
 - transmission time, 315–316
 - use of, 23, 295, 298
 - Circuits, 310, 303, 310, 321–313, 318–319
 - disconnect, 301
 - establishment, 301, 303
 - virtual, 310, 321–313, 318–319
 - Classifier, DS traffic conditioning function, 642–643
 - Clear to Send (CTS), IEEE 802.11 MAC, 540, 542
 - Client, SIP, 812
 - Clocking, 143–144
 - Coaxial cable, 112, 456
 - baseband, 456
 - broadband, 456
 - guided transmission media, 112
 - Code, 147, 162–165, 187–188, 196–201, 254, 275, 276, 287–290, 558, 715–716. *See also* Digital signal encoding; Encoding
 - block code principles, 197–201
 - division multiple access (CDMA), 275, 276, 287–290
 - division multiplexing (CDM), 276
 - error-correcting, 196–201
 - error-detecting, 187–188, 558
 - Manchester, 147
 - message authentication (MAC), 715–716
 - pulse code modulation (PCM), 162–165, 254
 - rate, 199
 - redundancy, 199
 - Code division multiple access (CDMA), 275, 276, 287–290, 429–436
 - advantages for cellular network, 430
 - cellular systems, 429–436

- defined, 275
 - DSSS, use for, 289–290
 - forward link, 432–434
 - frequency diversity, 430
 - graceful degradation, 430
 - IS-95 scheme, 432–436
 - mobile wireless design, 430–431
 - multipath resistance, 430
 - near-far problems, 430
 - orthogonal property, 288
 - principles of, 287–289
 - privacy, 430
 - RAKE receiver, 431
 - reverse link, 435–436
 - self-jamming, 430
 - use of, 276
 - Code division multiplexing (CMA), 276
 - Codec (coder-decoder), 162
 - Codeword, defined, 197
 - Coding, 545–546, 804
 - Huffman, video compression, 804
 - IEEE 802.11a, 545–546
 - Collocated network operation, wireless LANs, 528
 - Color subsampling, video compression, 803
 - Combined station, HDLQ, 222
 - Commands, SMTP, 748
 - Committed burst size, 391
 - Committed information rate (CIR), frame relays, 390–392
 - Communications network, 299–300
 - defined, 299
 - nodes, 299, 300
 - public telecommunications, 302–303
 - stations, 299
 - switched, 299–300
 - Complementary code keying (CCK), 547–548
 - Compression, 52, 729, 800–808
 - audio, 801–802
 - lossless, 801
 - lossy, 801
 - Moving Pictures Experts Group (MPEG), 801
 - multimedia, 52, 800–808
 - pulse amplitude modulation (PAM), 801
 - pulse code modulation (PCM), 801
 - SSL Record Protocol, 729
 - video, 803–808
 - Computer-aided design (CAD), 15
 - Computer Emergency Response Team (CERT) Coordination Center (CERT/CC), 732
 - Computer security, 703
 - Confidentiality, 703, 705–713. *See also* Symmetric encryption
 - Configuration, 29–31, 201–203, 222, 495, 528, 529–530
 - balanced, HDLQ, 222
 - diffused, IR LANs, 530
 - dynamic, LANs, 528
 - Ethernets, mixed, 495
 - example of, 29–31
 - infrared (IR) LANs, 529–530
 - line, 201–203
 - omnidirectional, IR LANs, 529
 - spread spectrum LANs, 530
 - unbalanced, HDLQ, 222
 - Confirm primitive, 47
 - Confirmed service, defined, 48
 - Conformance, GFR, 408
 - Congestion, adaptive routing, 360
 - Congestion avoidance, frame relays, 389, 393–394
 - Congestion control, 296, 377–412, 640–641, 683–693, 826
 - ATM traffic management, 394–406
 - ATM-GFR traffic management, 406–408
 - backpressure, 384
 - choke packet, 384–385
 - DS queuing, 640–641
 - dynamic window sizing, 691
 - effects of, 379–383
 - explicit signaling, 385–386, 389, 393–394
 - exponential average, 684–686
 - exponential RTO backoff, 688–689
 - fast recovery, 693
 - fast retransmit, 691–693
 - frame relays, 388–394
 - ideal performance, 381–382
 - implicit signaling, 385, 389
 - introduction to, 296, 378–379
 - Jacobson's algorithm, 686–688
 - Karn's algorithm, 689–690
 - packet-switching networks, 387–388
 - practical performance, 382–383
 - recommended reading, 409
 - retransmission timer (RTO), 686
 - retransmission timer management, 683–690
 - RTP Control Protocol (RTCP), 826
 - round-trip time (RTT), 684
 - RTT variance estimation, 686–688
 - simple average, 684
 - slow start, 690–691
 - TCP, 683–693
 - techniques, 383–386
 - traffic management, 386–387, 389–392, 394–406, 406–408
 - traffic rate management, 389–392
 - window management, 690–693
 - Congestion recovery, frame relays, 389
 - Connection, 399, 402–404, 559–561, 564, 663–665, 673–674, 680, 749–750, 751
 - admission control, ATM, 402–404
 - connection closing, SMTP, 751
 - control, protocol function, 559–561
 - duration, traffic and congestion control, 399
 - establishment, 663, 680
 - identifiers, addressing, 564
 - logical, ATM, 331–335
 - reliable network transport, 663–665
 - retransmit-SYN timer, 670
 - setup, SMTP, 749–750
 - TCP, 680
 - termination, 663–665, 673–674, 680
 - three-way handshake procedure, 671–673
 - unreliable network transport, 673–674
 - Connection-mode service, LLC, 460, 461
 - Connection-oriented mechanisms, *see* Network service
 - Connectionless operation, 460–461, 568–569, 570–571
 - acknowledged service, 460, 461
 - internetworking, 568–569
 - IP approach, 570–571
 - unacknowledged service, 460–461
 - Constant bit rate (CBR), 336, 345, 346, 402–403
 - connection admission control, 402–403
 - GFC mechanism, 336
 - real-time service, 345, 346
 - Content types, MIME, 753–757
 - Contention, MAC traffic approach, 464
 - Contention-Free (CF)-end, IEEE 802.11 MAC, 542
 - Contributing source (CSRC), 824–825
 - count, 824
 - identifier, 825
 - Control channels, cellular wireless networks, 420
 - Control field, 224, 464
 - HDLC, 224
 - MAC, 464
 - Control frames, 802.11 MAC, 541
 - Control module (SM), wireless LANs, 524
 - Control plane, 321, 330
 - ATM, 330
 - frame relay, 321
 - Control signaling, 335
 - Control unit, circuit switching, 305
 - Controlled cell transfer (CCT), ATM, 330
 - Controlled load service, ISA, 633
 - CRC, *see* Cyclic redundancy check (CRC)
 - Cross-building interconnect, wireless LANs, 525
 - Crosstalk, 90
 - CSMA, *see* Carrier sense multiple access (CSMA)
 - CSMA/CD, *see* Carrier sense multiple access with collision detection (CSMA/CD)
 - Customer premises equipment (CPE), defined, 26–27, 28
 - Cut-through switch, 476
 - Cyclic redundancy check (CRC), 189–196
 - digital logic, 194–196
 - polynomial division, 192–193
 - modulo 2 arithmetic, 189–192
- D**
- Damaged frame, 216
 - Data, defined, 78
 - DATA command, SMTP, 750
 - Data communications, 1–8, 9, 10–31, 62–64, 65–101, 102–137, 138–179, 180–206, 207–238, 239–273, 274–294. *See also* Digital data communication; Encoding; Signals
 - bottom-up versus top-down approaches to, 3–5
 - capacity requirements, 14
 - configuration, example of, 29–31
 - corporate wide area networking (WAN), 15
 - course emphasis, 3
 - data link control, 207–238
 - digital, 180–206
 - digital electronics, 15–16
 - encoding, 138–179
 - high-speed LANs, emergence of, 14–15
 - industry standards, 6–8
 - Internet, 25–29
 - introduction to, 11
 - model of, 16–18, 19–20
 - multiplexing, 239–273
 - networking and, 12–16

- Data communications (*cont.*)
 - networks, 22–24
 - outline of book, 2
 - overview of, 9
 - reader's and instructors guide, 1–8
 - services, 12–13
 - spread spectrum, 274–294
 - traffic, 12
 - transmission, 17, 20–21, 65–101, 102–137, 182–186
 - trends, 12–13
 - Web and Internet resources, 5–6
- Data Encryption Standard (DES), 707
- Data field, IP protocol, 579
- Data frame, 214–215, 542
 - 802.11 MAC, 542
 - flow control using, 214–215
- Data integrity, digital transmission, 86
- Data length, 574, 577
 - IP fragmentation and reassembly, 574
 - IP protocol, 577
- Data link connection identifier (DLIC), frame relay, 323
- Data link control protocols, 207–238
 - addressing, 208
 - automatic repeat request (ARQ), 216–221, 236–238
 - bit length of data link, 211
 - control and data on same link, 209
 - data link control, 207–238
 - defined, 208
 - error control, 208, 216–221
 - flow control, 208, 209–216, 232–236
 - frame synchronization, 208
 - high-level data link control (HDLC), 222–228
 - introduction to, 208–209
 - link management, 209
 - performance issues, 232–238
 - recommended reading, 228–229
 - sliding-window flow control, 212–216, 234–236
 - stop-and-wait flow control, 210–212, 232–234
- Data networks, congestion control in, 377–412
- Data Offset, TCP, 677
- Data packet, 58
- Data signaling rate, 141
- Data stream push, 675
- Data transfer, 226, 301, 322–323, 680, 822–826
 - circuit switching, 301
 - fixed header, RTP, 824–826
 - frame relay, 322–323
 - HDLC, 226
 - mixer, RTP
 - RTP protocol, 822–826
 - sessions, RTP, 823
 - TCP, 680
 - translator, RTP, 824
 - user, 322–232
- Data transmission, 65–101, 138–179
 - analog, 78–86, 162–168, 168–174
 - audio, 78, 81–82
 - binary, 82–83
 - capacity utilization, 86
 - channel capacity, 91–96
 - concepts and terminology of, 67
 - data integrity, 86
 - data rate and bandwidth, relationship between, 72–78
 - decibels and signal strength, 99–101
 - defined, 78
 - digital, 78–86, 141–151, 151–161
 - encoding, 138–179
 - frequency, 67, 68–69, 70–72, 77
 - impairments, 86–91
 - integration, 86
 - interlacing bandwidth, 79
 - introduction to, 66–67
 - key terms for, 141–142
 - privacy, 86
 - recommended reading and Web site, 96
 - security, 86
 - signals, 67–72, 78, 80–86, 86–91, 99–101
 - text, 79
 - video, 78–79, 82–83
- Data transparency, 224
- Data types, SNMPv2, 767
- Data Unit Identifier (ID), 574
- Database, DNS, 777–778
- Datagrams, 25, 38–39, 41, 310–311, 573.
 - See also* Packets
 - Internet use of, 25
 - IP design, 573
 - lifetime, 573
 - packet switching, approach to, 310, 311
 - segments, IP, 38
 - UDP, 38–39
- DCF, *see* Distributed coordination function (DCF)
- Deauthentication, IEEE 802.11, 550
- Decibels, 99–101
 - dBm (decibel-milliWatt), 101
 - dBmV (decibel millivolt), 101
 - dBW (decibel-Watt), 101
 - gain, 100
 - loss, 100
 - signal strength and, 99–101
- Decision time and place, routing, 355
- Delay, 52, 60, 87, 89, 315–316, 366–367, 395–398, 402–403, 514–517, 537–540, 628, 809–810
 - ARAPNET metrics, 366–367
 - cell delay variation (CDV), 395–398, 402–403
 - circuit and packet switching, 315–316
 - defined, 52
 - distortion, 87, 89
 - high-speed LANs, 514–517
 - inelastic traffic, 52, 628
 - interframe space (IFS), 537–540
 - intersymbol interference, 87
 - jitter, 809–810
 - node, 315–316
 - propagation, 315–316, 514–517
 - TFTP, 60
 - traffic management, ATM, 395–398, 402–403
 - transmission impairment from, 87, 89
 - transmission time, 315–316
 - variation, 52
- Deliver policy, TCP, 681
- Delivery, 534–535, 536, 561, 666
 - MAC service data units (MSDU), 534–535
 - ordered, 561, 666
 - reliable data, IEEE 802.11, 536
- Delta modulation (DM), 165–167
- Denial of service (DoS), 646, 704
- Dense wavelength division multiplexing (DWDM), 12, 247–248
- Destination, defined, 17
- Destination address, 38, 464, 490, 541, 577, 591
 - IEEE 802.11 MAC, 541
 - IEEE 802.3, (DA), 490
 - IP protocol, 577, 579
 - IPv6, 591
 - MAC, 464
 - subnetwork, 38
- Destination Options header, IPv6, 588, 595
- Destination port, TCP, 37, 676
- Destination unreachable message, ICMP, 584
- Differential encoding, 144–145
- Differential Manchester, 147
- Differentiated Services (DS)
 - architecture, 604, 636–645
 - codepoint, 639–640
 - configuration and operation of, 641–643
 - congestion control, 640–641
 - fields, 639–641
 - Per-hop behavior (PHB), 642–645
 - queue service, 640
 - queuing discipline, 640
 - route selection, 640
 - service level agreement (SLA), 637–639
 - services of, 637–639
 - terminology for, 638
 - traffic conditioning functions, 642–643
 - use of, 604, 636–637
- Diffraction, mobile communication, 425
- Digital, 68, 78–86, 139, 140, 141–151, 151–161, 162–168, 253–255, 304–305, 429. *See also* Digital data communication; Encoding
 - binary data, 82–83
 - capacity utilization, 86
 - carrier systems, TDM, 253–255
 - clarification of term, 66, 78
 - data integrity, 86
 - data, 78–86, 140, 141–151, 151–161
 - integration with analog data, 86
 - International Reference Alphabet (IRA), 79–80
 - privacy, 86
 - security, 86
 - signal, 68, 80–86, 140, 141–151, 162–168
 - signaling, 139
 - switch, 304–305
 - technology, 86
 - text, 79
 - traffic channels, 429
 - transmission, 85–86
- Digital data communication, 180–206
 - asynchronous transmission, 181, 182–185
 - block code principles, 197–201
 - correction of errors, 181, 196–201
 - cyclic redundancy check (CRC), 189–196
 - detection of errors, 181, 186–196
 - errors, 186–201
 - full-duplex transmission, 203
 - half-duplex transmission, 202–203
 - introduction to, 181–182
 - line configurations, 201–203
 - parity check, 188–189
 - recommended reading, 203
 - synchronization, 181

- synchronous transmission, 181, 182–183, 185–186
 - techniques, 180–206
 - topology, 201–202
 - Digital logic, 194–196
 - Digital signal encoding, 508–514
 - block-coding methods, 511
 - 8B6T, 511–513
 - 8B/10B, 513
 - 4B/5B-NRZI, 508–510
 - high-speed LANs, 508–514
 - MLT-3 scheme, 510–511
 - nonreturn to zero inverted (NRZI), 508–510
 - 64B/66B, 513–514
 - Digital signatures, 722–723
 - Digital versatile disks (DVDs), 15–16
 - Digitization, 162
 - Dijkstra's algorithm, 368–370, 371–372
 - Direct broadcast satellite (DBS), 122
 - Direct current (dc) component, 72, 836
 - Direct link, defined, 67
 - Direct sequence spread spectrum (DSSS), 275, 282–286, 289–290, 543, 544
 - Barker sequence, 544
 - BPSK, using, 282–284
 - CDMA use for, 289–290
 - defined, 275
 - exclusive-OR (XOR), use of, 282
 - IEEE 802.11 physical layer, 543, 544
 - performance considerations, 284–286
 - Directed-beam IR LANs, 529
 - Discard eligibility (DE), frame relays, 390
 - Discard policy, IAS, 629
 - Discard strategy, frame relays, 389
 - Disconnect (DISC) frame, HDLC, 226
 - Discrete cosine transformation (DCT), video compression, 803–804
 - Discrete multitone (DMT), 267–268
 - Disparity control, 8B/10B encoding, 513
 - Distance-vector routing, 616
 - Distributed coordination function (DCF), 536, 537–540
 - interframe space (DIFS), 539
 - Mac sublayer, 536, 537–540
 - Distributed foundation wireless MAC (DFWMAC), 536
 - Distribution system (DS), 532, 534–535
 - 802.11 model, 532, 534–535
 - defined, 534
 - integration, 534–535
 - messages distributed within, 534–535
 - Diversity, 427, 430
 - fading, 427
 - frequency, 427, 430
 - space, 427
 - DNS, *see* Domain Name System (DNS)
 - Domain, 67–70, 70–72, 775–777
 - defined, 775
 - frequency, 67, 70–72
 - Internet, 776
 - names, DNS, 775–777
 - signal transmission, 67–70, 70–72
 - time, 67–70
 - Domain Name System (DNS), 700, 774–784
 - database, 777–778
 - defined, 774
 - domain names, 775–777
 - messages, 782–784
 - name resolution, 782
 - operation, 779–784
 - recommended reading and Web site, 795–796
 - resource records (RRs), 777–778
 - server hierarchy, 779–782
 - use of, 700, 744
 - zone, 779–781
 - Don't fragment identifier, IP protocol, 577
 - Dotted decimal notation, IP addresses, 580
 - Driver, MLT-3 encoding, 510
 - Dropper, DS traffic conditioning function, 642–643
 - DS/ECN field, 578, 590
 - DSSS, *see* Direct sequence spread spectrum (DSSS)
 - Duplicate detection, unreliable network service, 667–668
 - Duration/Connection ID, IEEE 802.11 MAC, 541
 - Dynamic configuration, LANs, 528
 - Dynamic window sizing, TCP congestion control, 691
- E**
- Echo/echo reply message, ICMP, 584–585
 - Effective bandwidth, *see* Bandwidth
 - 8B6T encoding, 511–513
 - 8B/10B encoding, 513
 - Elastic traffic, 51–52, 625–628
 - ISA, 625–628
 - multimedia, 51–52
 - Electromagnetic spectrum, 105
 - Electromagnetic waves, 125
 - Electronic mail, 699, 744–760, 770–772
 - introduction to, 699, 744
 - Multi-Purpose Internet Mail Extension Protocol, 744, 752–760
 - operation of, 745–747
 - recommended reading and Web site, 770–771
 - Simple Mail Transfer Protocol (SMTP), 744, 745–752
 - Encapsulating Security Payload (ESP), 588, 599, 736
 - IPSec protocol, 599
 - IPv6 header, 588
 - network security format, 736
 - Encapsulation, protocol function, 558
 - Encoder, MLT-3 encoding, 510
 - Encoding, 138–179, 508–514, 757–760, 804. *See also* Digital signal encoding
 - amplitude modulation (AM), 169–171
 - amplitude shift keying (ASK), 151–152
 - analog data, analog signals, 140–141, 168–175
 - analog data, digital signals, 140, 162–168
 - analog signaling, 139
 - angle modulation, 171–174
 - baseband signal, 140
 - base64, 758–760
 - biphase, 147–148
 - bit error rate (BER), 142
 - carrier signal, 139
 - clocking, 143–144
 - codec (coder-decoder), 162
 - cost and complexity of, 144
 - delta modulation (DM), 165–167
 - differential Manchester, 147
 - differential, 144–145
 - digital data, analog signals, 140, 151–161
 - digital data, digital signals, 140, 141–151
 - digital signal, LANs, 508–514
 - digital signaling, 139
 - 8B6T, 511–513
 - 8B/10B, 513
 - error detection, 144
 - evaluation of techniques, 142–144
 - frequency modulation (FM), 171–174
 - frequency shift keying (FSK), 152–154
 - introduction to, 139–141
 - Manchester code, 147
 - MLT-3, 510–511
 - modulation, 139–140, 141, 148–149, 162–165, 165–167, 169–171, 171–174
 - multilevel binary, 146–147
 - noise immunity, 144
 - nonreturn to zero (NRZ), 144–145, 508
 - nonreturn to zero inverted (NZRI), 508–509
 - performance of digital-to-analog, 158–160
 - phase modulation (PM), 171–174
 - phase shift keying (PSK), 154–158
 - pulse code modulation (PCM), 162–165
 - quadrature amplitude modulation (QAM), 161
 - quoted-printable transfer, 757–758
 - recommended reading, 175
 - run-length, video compression, 804
 - sampling theorem, 162
 - scrambling, 149–151
 - signal interference, 144
 - signal spectrum, 143
 - signal techniques, 138–179
 - 64B/66B, 513–514
 - transfer, MIME, 757–760
 - Encryption, 702, 705–713, 714, 720–727, 729
 - Advanced Encryption Standard (AES), 707–710
 - algorithms, 705, 707–710, 723–726
 - confidentiality and, 705–713
 - Data Encryption Standard (DES), 707
 - devices, location of, 710–711
 - key management, 726–727
 - message authentication and, 714
 - public-key, 702, 720–727
 - RSA algorithm, 723–726
 - SSL Record Protocol, 729
 - symmetric, 702, 705–713, 714
 - End system (ES), 566
 - Entities, HTTP, 794–795
 - Envelope, SMTP, 754
 - Error, 18, 58, 60, 92, 94–96, 142, 144, 163–164, 181, 184, 186–196, 196–201, 208, 216–221, 236–238, 426–427, 558, 621
 - adaptive equalization, 426–427
 - automatic repeat request (ARQ), 216–221, 236–238
 - BGB Notification Message, 621
 - bit error rate (BER), 142
 - block code principles, 197–204

- Error (*cont.*)
 burst, 186
 channel capacity, 92, 94–96
 check bits, 187–188
 code for detecting, 187–188
 codeword, 197
 compensation mechanisms, fading,
 426–427
 correction of, 18, 181, 196–201
 cyclic redundancy check (CRC),
 189–196
 damaged frame, 216
 detecting code, 558
 detection, 18, 144, 181, 186–196,
 216
 digital data communication,
 186–201
 digital logic, 194–196
Eb/NO expression, 94–96
 forward correction, 426
 framing, 184
 lost frame, 216
 modulo 2 arithmetic, 189–192
 negative acknowledgement, 216
 packet, 58
 parity check, 188–189
 polynomial division, 192–193
 positive acknowledgement, 216
 quantizing noise, 163–164
 rate, 92, 94–96
 retransmission after timeout, 216
 single-bit, 186
 TFTP, 60
- Error control, 208, 216–221, 236–238,
 338, 339–340, 561–562, 576
 automatic repeat request (ARQ),
 216–221, 236–238
 data link control protocols, 208,
 216–221
 frames, 216–221
 Header Error Control (HEC) field,
 ATM, 338, 339–340
 IP design, 576
 protocol function, 561–562
- Ethernets, 483, 485–500
 ALOHA, 485
 carrier sense multiple access
 (CSMA), 486–490
 collision, 485
 CSMA/CD, 483, 488–490
 defined, 483
 Fast, 483, 493–493
 full duplex operation, 494–495
 Gigabit, 483, 495–497
 IEEE 802.3, 485–495
 MAC frame, IEEE 802.3 protocol,
 490–492
 medium access control (MAC),
 485–492
 mixed configurations, 495
 100BASE-T4, 494
 100BASE-X, 494
 100-Mbps specifications, 493
 precursors to, 485–488
 10-Gbps, 497–500
 10-Mbps specifications, 492–493
- Excess burst size, 391
- Exchanges, 18, 302–303, 599, 621–623,
 730–732
 Handshake Protocol, 730–732
 key, IPsec, 599
 management, 18
 public telecommunications network,
 302–303
 routing information, BGP, 621–623
- Exclusive-OR (XOR), DSSS, 282
- Expedited forwarding (EF) PHB,
 643–644
- Explicit Congestion Notification
 (ECN) field, 578
- Explicit congestion signaling, 385–386,
 389, 393–394
 backward, 385–386
 backward explicit congestion notifi-
 cation (BECN), 393
 binary, 386
 congestion avoidance, 389, 393–394
 credit-based, 386
 forward, 386
 forward explicit congestion notifica-
 tion (FECN), 393
 rate-base, 386
- Exponential average, TCP congestion
 control, 684–686
- Exponential RTO backoff, 688–689
- Extended service set (ESS), 802.11
 model, 533
- Exterior router protocol (ERP), 616
- F**
- Fabric, Fibre Channel network, 502
- Facility requests, 38
- Fading, 424–427
 defined, 422
 diffraction, 425
 diversity, 427
 error compensation mechanisms,
 426–427
 fast, 426
 flat, 426
 mobile environment, in, 424
 multipath propagation, 424–426
 reflection, 424
 scattering, 425
 selective, 426
 slow, 426
 types of, 426
- Failure, adaptive routing, 360
- Failure recovery, unreliable network
 service, 674
- Fairness, congestion traffic
 management, 386–387
- Fast Ethernet, 483, 493–493
- Fast fading, 426
- Fast forward/reverse searches, video
 compression, 804
- Fast recovery, TCP congestion control,
 693
- Fast retransmit, TCP congestion
 control, 691–693
- FDM, *see* Frequency division
 multiplexing (FDM)
- Federal Communications Commission
 (FCC) licensing, 528, 530
- FHSS, *see* Frequency-hopping spread
 spectrum (FHSS)
- Fiber optic transmission, *see* Optical
 fiber transmission
- Fibre Channel, 483, 500–504
 elements, 502–503
 fabric, 502
 I/O channel requirements, 500–501
 network channel requirements,
 501–502
 nodes, 502
 prospects for, 504
 protocol architecture, 503
 topologies, 504
 transmission media, 503
- Fields, 223–224, 577–579, 611–613,
 620–621, 676–679
 BGP Path Attributes, 620–621
 HDLC, 223–224
 IGMP, 611–613
 IP, 577–579
 TCP, 676–679
- File Transfer Protocol (FTP), 41, 48
- First-in-first-out queuing (FIFO),
 633–634
- Fixed routing, 356–357, 468–471
- Flag and Frame Check Sequence
 (FCS) field, frame relay, 323
- Flags, 223–224, 578, 677, 679
 HDLC, 223–224
 IP protocol, 578
 TCP, 677, 679
- Flat fading, 426
- Flooding, routing strategy of, 357–359
- Flow control, 18, 208, 209–216,
 232–236, 561, 576, 659–663,
 668–673
 acknowledgment number (*AN*), 661
 data link control protocol, 208,
 209–216
 defined, 18, 208
 IP design, 576
 performance issues, 232–238
 persist timer, 669
 protocol function, 561
 reliable network service transport,
 659–663
 sequence number (*SN*), 661
 sliding-window, 212–216, 234–236
 stop-and-wait, 210–212, 232–234
 unreliable network service, 668–673
 window (*W*), 661
- Flow label, IPv6, 590, 591–592
- Forward explicit congestion
 notification (FECN), 393
- 4B/5B-NRZI encoding, 508–510
- Four-level PSK, *see* Quadrature phase-
 shift keying (QPSK)
- Fourier analysis, 835–840
 aperiodic signals, 837, 839–840
 periodic signals, 836–837, 838
 recommended reading, 840
 series representation, 836–837, 838
 transform representation, 837,
 839–840
- Fragment header, IPv6, 588, 594–595
- Fragment Offset field, IP protocol,
 578–579
- Fragmentation and reassembly,
 558–559, 573–576, 729
 Data Length, 574
 Data Unit Identifier (ID), 574
 IP design, 573–576
 More Flag, 574, 575
 Offset, 574, 575
 protocol function, 558–559
 SSI Record Protocol, 729
- Frame Check Sequence (FCS), 492,
 541
- Frame forwarding, 471
- Frame ordering, video compression,
 807–808
- Frame relay, 23, 319–323, 388–394
 Address field extension (EA), 323
 background of, 320–321
 backward explicit congestion notifi-
 cation (BECN), 393
 committed burst size, 391
 committed information rate (CIR),
 390–392

- congestion avoidance, 389, 393–394
- congestion control, 388–394
- congestion recovery, 389
- control plane, 321
- data link connection identifier (DLIC), 323
- discard eligibility (DE), 390
- discard strategy, 389
- excess burst size, 391
- explicit signaling, 393–394
- Flag and Frame Check Sequence (FCS) field, 323
- forward explicit congestion notification (FECN), 393
- implicit signaling, 389
- network response, 393
- networks and, 23
- protocol architecture, 321–322
- traffic rate management, 389–392
- user data transfer, 322–323
- user plane, 321–322
- user response, 393–394
- Frame structure, physical layer, 546, 548
- Frame transmission, LAN topologies, 453–455
- Frames, 185, 208, 213, 214–215, 216–221, 223–225, 250–252, 256–258, 259, 256–258, 259, 485, 490–492, 496, 541–543, 807–808
- acknowledgement, 215
- anchor frame, video compression, 805
- bursting, Gigabit Ethernet, 496
- check sequence (FCS) field, HDLC, 225
- collision, 485
- control, 542
- damaged, 216, 219
- data, 214–215, 542
- defined, 185
- error control, 216–221
- formats, TDM, 256–258, 259
- high-speed LANs, 490–492
- IEEE 802.11 format, 541–543
- IEEE 802.3 protocol, 490–492
- information (I-frames), 224
- lost, 216
- MAC, 490–492, 541–543
- management, 534
- ordering, video compression, 807–808
- SONET/SDH formats, 256–258
- statistical TDM formats, 259
- structure, HDLC, 223–225
- supervisory (S-frames), 224
- synchronization, 208
- TDM, 250–252
- unnumbered (U-frames), 224
- window of, 213
- Framing, 184, 251–252
- error, asynchronous transmission, 184
- link control, TDM, 251–252
- Free space loss, 129–132
- Frequency, 67, 68–69, 70–72, 77, 105, 116, 117, 126, 416–417, 427, 430, 836
- borrowing, 417
- center, 77
- dc component, 72
- defined, 68–69
- diversity, 427, 430
- domain, 67, 70–72
- fiber optic transmission, of, 116
- fundamental, 72, 836
- infrared, 117
- microwave, 117
- radio, 117
- reuse, 416–417
- spectrum, 72
- transmission media, of, 105
- wireless transmission bands, 126
- Frequency division multiplexing (FDM), 240, 241, 242–248
- analog carrier systems, 246–247
- channel, 243
- characteristics of, 242–246
- dense wavelength division multiplexing (DWDM), 247–248
- subcarrier, 243
- TV signals, 243–244
- use of, 240, 241
- voiceband signals, 244–246
- wavelength division multiplexing (WDM), 247–248
- Frequency-hopping spread spectrum (FHSS), 275, 277–282, 543, 544–545
- approach to, 277–279
- binary phase shift keying (BPSK), using, 277–278
- chipping signal, 279
- defined, 275
- frequency shift keying (FSK), using, 277–279
- IEEE 802.11 physical layer, 543, 544–545
- multiple phase shift keying (MFSK), using, 279–282
- performance considerations, 282
- pseudonoise (PN), 277
- Frequency modulation (FM), 171–174
- Frequency shift keying (FSK), 139, 152–154, 277–279, 279–282
- binary (BFSK), 152–154, 278
- defined, 139
- digital data, analog signal encoding, 152–154
- FHSS using, 277–279, 279–282
- full-duplex, 153
- multiple (MFSK), 153–154, 279–282
- signal encoding schemes, 152–154
- Full-duplex transmission, 67, 153, 203
- Fundamental frequency, 72
- G**
- Gateway, HTTP, 788
- General query, IGMP, 611
- Generic Flow Control (GFC), ATM cells, 336, 338–339
- GFR, *see* Guaranteed frame rate (GFR)
- Gigabit Ethernet, 483, 495–497
- carrier extension, 495
- frame bursting, 496
- media access layer, 495–496
- physical layer, 496–497
- Global applicability, addressing, 563
- Global nonambiguity, addressing, 563
- Global Positioning System (GPS), 122–123
- Go-back-N ARQ, 217–221, 238
- Goodbye (BYE), RTCP, 828, 831
- Graceful degradation, CDMA, 430
- Ground wave propagation, 125, 127
- Group Address, IGMP, 611
- Group-and-source-specific query, 611
- Group record, IGMP, 612, 613
- Group-specific query, IGMP, 611
- Guaranteed frame rate (GFR), 345, 348, 406–408
- ATM service, 345, 348
- buffer management, 407
- conformance, 408
- policing, 407
- quality of service (QoS) eligibility test, 408
- rate guarantees, mechanisms for supporting, 406–407
- scheduling, 407–408
- tagging, 407
- traffic management, ATM, 406–408
- Guaranteed service, ISA, 632–633
- Guided transmission media, 67, 103, 104–116
- attenuation of, 108
- coaxial cable, 112
- defined, 67, 103
- optical fiber, 112–116
- point-to-point characteristics, 67, 104, 106
- twisted pair, 104–111
- H**
- Half-duplex transmission, 67, 202–203
- Hamming distance, 197
- Handoff, 422, 528
- MTSO, 422
- wireless LANs, 528
- Handshake, 670–673, 730–732
- connection establishment, 670–673
- Protocol, 730–732
- three-way procedure, 671–673
- Harmonics, defined, 836
- Hash functions, 716–720
- one-way, 716–717
- secure, 717–718, 720
- Secure Hash Algorithm (SHA), 718–720
- HDLC, *see* High-level data link control (HDLC)
- Headend, 264, 453
- cable, 264
- tree topology, 453
- Header checksum, IP protocol, 579
- Header Error Control (HEC) field, ATM, 338, 339–340
- Header fields, HTTP, 790–791, 792–793, 794, 794–795
- entities, 794–795
- general messages, 790–791
- request messages, 792–793
- response messages, 794
- Header section, DNS messages, 782–784
- Headers, 223, 336–338, 583, 590–592, 593–595, 676–679, 818–819, 819–820, 824–826
- fixed, RTP, 824–826
- ATM format, 336–338
- flow label, 591–592
- HDLC, 223
- ICMP, 583
- IPv6, 590–592, 593–595
- request messages, SIP, 818–819
- response messages, SIP, 819–820
- TCP, 676–679
- High data rate digital subscriber line (HDSL), 268–269
- High-density bipolar-3 zeros (HDB3), 150–151

- High-level data link control (HDLC), 222–228
 - address field, 224
 - asynchronous balanced mode (ABM), 222
 - asynchronous response mode (ARM), 222
 - basic characteristics of, 222
 - commands and responses, 225
 - control field, 224
 - data transfer, 226
 - data transparency, 224
 - disconnect (DISC), 226
 - flag fields, 223–224
 - frame check sequence (FCS) field, 225
 - frame structure, 223–225
 - header, 223
 - information field, 224–225
 - information frames (I-frames), 224
 - initialization, 226
 - normal response mode (NRM), 222
 - operation, 225–228
 - supervisory frames (S-frames), 224
 - trailer, 223
 - unnumbered frames (U-frames), 224
 - High-speed LANs, 14–15, 445, 450, 482–521. *See also* Wireless LANs
 - centralized server farms, 484
 - CSMA/CD model, 517–518
 - digital signal encoding, 508–514
 - emergence of, 14–15, 483–485
 - Ethernets, 483, 485–500
 - Fibre Channel, 483, 500–504
 - IEEE 802.3, 485–495
 - introduction to, 445, 483
 - local backbone, 15, 485
 - medium access control (MAC), 485–492
 - office networks, 450
 - performance issues, 514–518
 - power workgroups, 484
 - propagation delay, 514–517
 - recommended reading and Web sites, 504–506
 - scrambling, 518–521
 - transmission rate, 514–517
 - wireless, 483
 - High-speed local backbone, 15, 485
 - Hop-by-Hop Options header, IPv6, 588, 593–594
 - Hop Limit field, IPv6, 590
 - Host, network service, 25, 658
 - Host-to-host layer, TCP/IP, 35–36
 - HTTP, *see* Hypertext Transfer Protocol (HTTP)
 - Hubs, 447, 454, 473–475
 - header (HHUB), 473–474
 - intermediate (IHUB), 473–474
 - star topology, 454
 - switches and, 474–475
 - Huffman coding, video compression, 804
 - Hypertext Transfer Protocol (HTTP), 700, 774, 784–798
 - cache, 788
 - entities, 794–795
 - gateway, 788
 - key terms for, 785
 - messages, 788–794
 - origin server, 786
 - overview of, 784–788
 - proxy, 787
 - recommended reading and Web site, 795–796
 - tunnel, 788
 - use of, 700, 744, 784
 - user agent, 786
- I**
- ICMP, *see* Internet Control Message Protocol (ICMP)
 - Identification, IP protocol, 577
 - Identification field, IP protocol, 578
 - Identification function, RTPC, 826
 - Identifier restriction, VPC, 334
 - Idle code, NRZI encoding, 510
 - Idle state, defined, 183
 - IEEE 802, 457–460
 - LAN reference model, 457–460
 - logical link control (LLC) layer, 458–460
 - medium access control (MAC), 458–460
 - physical layer, 457
 - IEEE 802.11, 523, 531–535, 535–543, 543–549, 549–550
 - access and privacy services, 550
 - access point (AP), 532
 - architecture, 531–533
 - association-related services, 535
 - authentication, 550
 - basic services set (BSS), 532
 - deauthentication, 550
 - distribution system (DS), 532, 534–535
 - extended service set (ESS), 533
 - IEEE 802.11a, 543, 545–547
 - IEEE 802.11b, 547–548
 - IEEE 802.11g, 548–549
 - independent basic services set (IBSS), 532
 - MAC frame, 541–543
 - MAC service data units (MSDU) delivery, 534–535
 - medium access control (MAC), 534–535, 535–543
 - physical layer, 543–549
 - portal, 532
 - privacy, 550
 - reliable data delivery, 536
 - security considerations, 549–550
 - services, 533–535
 - Wi-Fi Protected Access (WPA), 550
 - Wired Equivalent Privacy (WEP) algorithm, 550
 - Wireless Fidelity (Wi-Fi) Alliance, 532
 - IEEE 802.3, 485–495
 - Ethernet specifications, 485–495
 - full duplex operation, 494–495
 - MAC frame for, 490–492
 - medium access control (MAC), 485–492
 - mixed configurations, 495
 - 100BASE-T4, 494
 - 100BASE-X, 494
 - 100-Mbps specifications, 493
 - 10-Mbps specifications, 492–493
 - IFS, *see* Interframe space (IFS)
 - IGMP, *see* Internet Group Management Protocol (IGMP)
 - Image, media type, 50
 - Image type, MIME, 756
 - Implicit congestion signaling, 385, 389
 - congestion recovery, 389
 - technique, 385
 - Impulse noise, 90–91
 - Independent basic services set (IBSS), 802.11 model, 532
 - Index of refraction, 128
 - Indication primitive, 47
 - Inelastic traffic, 51–52, 628
 - delay, 52, 628
 - ISA, 628
 - jitter, 628
 - multimedia, 51–52
 - packet loss, 52, 628
 - throughput, 51, 628
 - Information field, HDLC, 224–225
 - Information frames (I-frames), 224
 - Information security, 702–703
 - Infrared, 117, 125, 544, 545
 - frequency range, 125
 - IEEE 802.11 physical layer, 544, 545
 - pulse position modulation (PPM), 545
 - wireless transmission, 125
 - Infrared (IR) LANs, 528–530
 - defined, 528
 - diffused configuration, 530
 - directed-beam, 529
 - omnidirectional configuration, 529
 - strength and weaknesses of, 529
 - transmission techniques, 529–530
 - Institute of Electrical and Electronics Engineers (IEEE), 7, 457–460
 - 802 reference model, 457–460
 - introduction to, 7
 - Integrated Services Architecture (ISA), 604, 625–636
 - approach of, 628–629
 - classifier and route selection, packets, 630–631
 - components of, 629–631
 - controlled load service, 633
 - elastic traffic, 625–628
 - first-in-first-out queuing (FIFO), 633–634
 - functions, 629
 - guaranteed service, 632–633
 - inelastic traffic, 628
 - Internet traffic, 625–628
 - ITeF development of, 625
 - packet discard, 629
 - packet scheduler, 631
 - QoS transport, 625, 628–629
 - queuing discipline, 633–636
 - Resource ReSerVation Protocol (RSVP), 604, 635–636
 - routing algorithm, 629
 - services of, 631–633
 - traffic specification (Tspec), 631–632
 - use of, 604
 - weighted fair queuing (WFQ), 634
 - Integration, 22, 86
 - analog and digital data, 86
 - defined, 22
 - Integrity, defined, 703
 - Interface, defined, 17
 - Interference, 87, 104, 132–133
 - intersymbol, 87
 - multipath, wireless transmission, 132–133
 - transmission media and, 104
 - Interframe space (IFS), 537–540
 - CSMA, rules for access, 537–538
 - DCF delay, 537
 - distributed coordination function (DIFS), 539
 - point coordination function (PIFS), 539
 - short (PIFS), 539

- Interior router protocol (IRP), 615–616
- Interlacing, bandwidth technique, 79
- Intermediate system (IS), 566–567
- Intermodulation noise, 90
- International Organization for Standardization, *see* ISO
- International Reference Alphabet (IRA), 79–80
- International Telecommunications Union (ITU), 8, 255
 - introduction to, 8
 - Telecommunication Standardization Sector (ITU-T), 8, 255
- Internet, 25–29, 554–555, 556–602, 603–654, 699–833
 - applications, 699–833
 - architecture, 25–29
 - central office (CO), 27, 28
 - customer premises equipment (CPE), 26–27, 28
 - defined, 566
 - Differentiated Services (DS) architecture, 604, 636–645
 - hosts, 25
 - Integrated Services Architecture (ISA), 604, 625–636
 - internetwork operation, 603–654
 - IP address, 25
 - IP datagrams (packets), 25
 - IPv6, 586–595
 - key elements of, 25
 - network access point (NAP), 28–29
 - network service provider (NSP), 28–29
 - origins of, 25
 - point of presence (POP), 26, 27–28
 - protocols, 554–555, 556–602
 - routers, 25
 - security (IPSec), 596–599, 732–736
 - service provider (ISP), 26, 27–28
 - traffic, 625–628
 - virtual private networks (VPN), 596–599
- Internet Applications, 699–700, 701–742, 743–772, 773–798, 799–833
 - Domain Name System (DNS), 700, 774–784
 - electronic mail, 699, 744–760
 - Hypertext Transfer Protocol (HTTP), 700, 774, 784–798
 - Internet directory service, 700, 774–784
 - multimedia, 700, 799–833
 - Multi-Purpose Internet Mail Extension Protocol (MIME), 744, 752–760
 - network management, 699, 744, 760–772
 - network security, 699, 701–742
 - Simple Mail Transfer Protocol (SMTP), 41, 48, 744, 745–752
 - Simple Network Management Protocol (SNMP), 744, 760–770
 - Web access, 700, 774, 784–798
- Internet Architecture Board (IAB), 7, 596, 732
- Internet Control Message Protocol (ICMP), 582–585
 - address mask request/reply, 585
 - destination unreachable, 584
 - echo/echo reply, 584–585
 - headers, 583
 - parameter problem, 584
 - redirect, 584
 - source quench, 584
 - time exceeded, 583
 - timestamp/timestamp reply, 585
- Internet directory service, *see* Domain Name System (DNS)
- Internet Engineering Task Force (IETF), 7, 39, 625, 646–649
 - introduction to, 7
 - IP Performance Metrics (IPPM) Working Group, 646–649
 - IPv6, development of, 39
 - ISA development, 625
- Internet Group Management Protocol (IGMP), 610–614
 - general query, 611
 - group-and-source-specific query, 611
 - group record, 612, 613
 - group-specific query, 611
 - IPv6, group membership with, 614
 - Membership Query message, 611–613
 - Membership Report message, 612, 613
 - message format, 611–613
 - operations, 613–614
 - use of, 610–611
- Internet Header Length (IHL), IP protocol, 578
- Internet Protocol (IP), 35, 39–40, 554–555, 556–602
 - Address Resolution Protocol (ARP), 585–586
 - addresses, 579–582
 - base functions, 558–565
 - connectionless internetworking, 570–571
 - data unit identifier (ID), 574
 - datagram lifetime, 573
 - design issues, 572–576
 - error control, 576
 - fields, 577–579
 - fragmentation and reassembly, 573–576
 - headers, 39–40
 - Internet Control Message Protocol (ICMP), 582–585
 - internetworking, principles of, 566–569
 - introduction to, 554–555, 557
 - IPv6, 39–40, 586–595
 - layer, 35
 - next-generation, 557, 586–588
 - operation, 569–576
 - recommended reading and Web sites, 599–600
 - routing, 573
 - security (IPSec), 596–599
 - service primitives, 576–577
 - virtual private networks (VPN), 596–599
- Internet Society (ISOC), 7
- Internetwork operation, 554–555, 603–654
 - autonomous system (AS), 614–616, 623–625
 - Border Gateway Protocol (BGP), 618–623
 - Differentiated Services (DS) architecture, 604, 636–645
 - Integrated Services Architecture (ISA), 604, 625–636
 - introduction to, 554–555, 604–605
 - IP performance metrics, 646–649
 - multicasting, 604, 605–614
 - Open Shortest Path First (OSPF) Protocol, 623–625, 626, 627
 - queuing, 633–636, 640–641
 - recommended reading and Web sites, 649–651
 - routing protocol, 604, 614–625, 626, 627
 - RSVP, 604
 - service level agreements (SLA), 645–646
- Internetworking, principles of, 566–569
 - bridge, 567
 - connectionless operation, 568–569
 - end system (ES), 566
 - intermediate system (IS), 566–567
 - requirements of, 567–568
 - router, 567
 - terms for, 566
- Interpolation, video compression, 806–807
- Intersymbol interference (ISI), 87, 425–426
- IP, *see* Internet Protocol (IP)
- IP address, defined, 25
- IP security (IPSec), 596–599, 732–736
 - applications of, 596–597, 598, 732–733
 - authentication header (AH), 599, 734–736
 - benefits of, 597
 - Computer Emergency Response Team (CERT) Coordination Center (CERT/CC), 732
 - Encapsulating Security Payload (ESP), 599, 736
 - functions, 599
 - Internet Architecture Board (IAB), 596, 732
 - key exchange, 599
 - parameters, 733–734
 - protocol, 596–599
 - scope of, 733
 - security association (SA), 733–734
 - security parameters index (SPI), 733
- IPv4 security, 732–736
- IPv6, 39–40, 557, 586–595, 732–736
 - addresses, 592–593
 - Authentication header, 588
 - Destination Options header, 588, 595
 - Encapsulating Security Payload header, 588
 - flow label, 590, 591–592
 - Fragment header, 588, 594–595
 - headers, 590–592, 593–595
 - Hop-by-Hop Options header, 588, 593–594
 - IETF development of, 39
 - Internet protocol and, 39–40
 - next generation IP, 557, 586–588
 - Routing header, 588, 595
 - security, 732–736
 - structure of, 588–589
- IS-95 CDMA scheme, 432–436
 - forward link, 432–434
 - reverse link, 435–436
- ISO, 8, 42
 - introduction to, 8
 - OSI model, development of, 42
 - Isotropic antenna, 117
- Iterative technique, DNS name resolution, 782
- ITU, *see* International Telecommunications Union (ITU)

- ITU Telecommunication Standardization Sector (ITU-T), 8, 255
 signal designations, SDH, 255
 use of, 8
- J**
 Jacobson's algorithm, 686–688
 Jitter, 628, 646, 809–810
 delay, 809–810
 inelastic traffic, 628
 network, 646
- K**
 Karn's algorithm, 689–690
 Keepalive timer, 674
 Key distribution, 711–713
 center, 713
 permanent key, 713
 security service module (SSM), 713
 session key, 712
 Key exchange, IPSec, 599
 Key management, 726–727
- L**
 LAN, *see* Local area network (LAN)
 Large-scale integration (LSI), 7, 86
 Latency/speed effects, traffic control, 395
 Least-cost algorithms, 367–372
 Bellman-Ford, 370–371, 371–372
 comparison of, 371–372
 Dijkstra's, 368–370, 371–372
 License-free operation, wireless LANs, 528
 Line configurations, 201–203
 full-duplex transmission, 203
 half-duplex transmission, 202–203
 topology, 201–202
 Line-of-sight (LOS), 125–129, 129–133
 atmospheric absorption, 132
 effective, 127
 free space loss, 129–132
 impairments, 129–133
 multipath interference, 132–133
 optical, 128–129
 propagation, 125–129
 radio, 128–129
 refraction, 128, 133
 transmission, 129–133
 Link Access Protocol-Balanced (LAPB), 318–319
 Link control, 250–253
 framing, 251–252
 pulse stuffing, 252–253
 TDM, 250–253
 Link management, defined, 209
 Link-state routing, 616–617
 LLC, *see* Logical link control (LLC)
 Local area network (LAN), 12, 14–15, 22, 444–445, 446–481, 482–521, 522–553
 backbone, 15, 450–451, 485, 527–528
 backend networks, 448–449
 background of, 448–451
 bridges, 465–473
 bus topology, 447, 451–453, 454
 digital signal encoding, 508–514
 extension, 524–525
 frame transmission, 453–455
 high-speed, 14–15, 445, 450, 482–521
 hubs, 447, 454, 473–474
 IEEE 802 reference model, 457–460
 infrared (IR), 528–530
 introduction to, 444, 447
 logical link control (LLC), 458–460, 460–463
 medium access control (MAC), 458–460, 463–465, 535–543
 overview of, 444, 446–481
 performance issues, 514–518
 personal computer, 448
 propagation delay, 514–517
 protocol architecture, 457–465
 recommended reading and Web site, 478–479
 ring topology, 447, 453, 455
 scrambling, 518–521
 spread spectrum, 528, 530
 star topology, 447, 454
 storage area network (SAN), 449
 switches, 447, 473–478
 topologies, 451–456
 transmission media, 451, 455–457
 transmission rate, 514–517
 tree topology, 447, 451–453
 trends of, 12
 use of, 22, 24, 444–445
 wireless, 445, 483, 522–553
 Local loop, defined, 27
 Local_Pref, 620
 Logical connections, ATM, 331–335
 control signaling, 335
 virtual channel connection (VCC), 331, 333–335
 virtual path connection (VPC), 331–333, 334–335
 Logical link control (LLC), 458–460, 460–463
 acknowledged connectionless service, 460, 461
 connection-mode service, 460, 461
 IEEE 802 reference model layer, 458–460
 protocol, 461–463
 protocol data unit (PDU), 460
 services, 460–461
 unacknowledged connectionless service, 460–461
 LOS, *see* Line-of-sight (LOS)
 Lossless compression, 801
 Lossy compression, 801
 Lost frame, 216
- M**
 MAC, *see* Medium access control (MAC)
 MAIL command, SMTP, 750
 Management agent, 630, 761–762
 ISA, 630
 SNMP, 761–762
 Management frames, IEEE 802.11
 MAC, 543
 Management information base (MIB), 762, 765, 767
 Management plane, ATM, 330
 Management station, SNMP, 761
 Manchester code, 147
 Marker, DS traffic conditioning
 function, 642–643
 Masquerade, network attack, 704
 Max Response Code, IGMP, 611
 Media access layer, Gigabit Ethernet, 495–496
 Media gateway (MG), 308–309
 Media gateway controller (MGC), 308–309
 Medium access control (MAC), 458–460, 463–465, 534–535, 535–543
 contention, 464
 distributed coordination function (DCF), 536, 537–540
 distributed foundation wireless (DFWMAC), 536
 frame, 460, 464–465, 541–543
 IEEE 802 reference model layer, 458–460
 IEEE 802.11 reference model, 534–535, 535–543
 interframe space (IFS), 537–540
 point coordination function (PCF), 536, 539, 540–541
 reliable data delivery, 536
 reservation, 464
 round robin, 464
 service data units (MSDU) delivery, 534–535
 Membership Query message, IGMP, 611–613
 Membership Report message, IGMP, 612, 613
 Message authentication, 713–720, 729
 approaches to, 714–717
 code (MAC), 715–716
 encryption, without, 714
 one-way hash function, 716–717
 Secure Hash Algorithm, 718–720
 secure hash functions, 717–718, 720
 SSL Record Protocol, 729
 symmetric encryption, using, 714
 Message type, MIME, 755–756
 Messages, 18, 534–535, 582–585, 611–613, 619–621, 704, 782–784, 788–794, 817–820
 additional records section, DNS, 783, 784
 answer section, DNS, 783, 784
 authority section, DNS, 783, 784
 Backus-Naur Form (BNF), 788–790
 distribution of within a distribution system (DS), 534–535
 Domain Name System (DNS), 782–784
 formatting, 18
 header fields, 790–791, 792–793, 794, 818–819, 819–820
 header section, DNS, 782–784
 Hypertext Transfer Protocol (HTTP), 788–794
 IGMP format, 611–613
 integrity with privacy, WPA, 739
 Internet Control Message Protocol (ICMP), 582–585
 Membership Query, IGMP, 611–613
 Membership Report, IGMP, 612, 613
 methods, 791–792, 817–818
 modification of, 704
 Notification, BGP, 621
 question section, DNS, 783, 784
 request, 791–793, 817–819
 response, 793–794, 819–820
 Session Initiation Protocol (SIP), 817–820
 status codes, HTTP, 793
 Meter, DS traffic conditioning
 function, 642–643
 MFSK, *see* Multiple frequency shift keying (MFSK)
 Microcells, defined, 418

- Microwave systems, 117, 119–124, 125–129, 132–133
 antenna, 119–120
 applications of, 119, 122–123
 direct broadcast satellite (DBS), 122
 frequency range, 117
 Global Positioning System (GPS), 122–123
 line of sight (LOS), 125–129, 132–133
 multipath interference, 132–133
 satellite, 120–124
 terrestrial, 119–120
 transmission characteristics of, 120, 123–124
 transponder channels, 121
 very small aperture terminal (VST), 122
- MIME, *see* Multi-Purpose Internet Mail Extension Protocol (MIME)
- Mixer, RTP relay, 824
- MLT-3 encoding, 510–511
- Mobile communication, 419–422, 422–424, 424–427
 environment, 424–427
 fading, 422, 424–427
 intersymbol interference (ISI), 425–426
 mobile telecommunications switching office (MTSO), 419–422
 multipath propagation, 424–426
 radio propagation effects, 422–424
 signal strength, 422
- Mobile telecommunications switching office (MTSO), 419–422
 call functions, 421–422
 handoff, 422
 mobile unit initialization, 420
 mobile-originated call, 420
 paging, 421
 remote mobile subscriber, calls to/from, 422
- Modulation, 139–140, 141, 148–149, 162–165, 165–167, 169–171, 171–174, 545–546, 547–548
 amplitude (AM), 169–171
 angle, 171–174
 baseband signal, 140
 carrier signal, 139
 complementary code keying (CCK), 547–548
 defined, 139–140
 delta (DM), 165–167
 frequency (FM), 171–174
 IEEE 802.11a, 545–546
 IEEE 802.11b, 547–548
 packet binary convolution coding (PBCC), 548
 phase (PM), 171–174
 pulse amplitude (PAM), 163–164
 pulse code (PCM), 162–165, 254
 pulse position (PPM), 545
 quadrature amplitude (QAM), 161
 quantizing noise, 163–164
 rate, 141, 148–149
- Modulo 2 arithmetic, 189–192
- More Flag, IP fragmentation and reassembly, 574, 575
- Motion compensation, video compression, 805
- Moving Pictures Experts Group (MPEG), 801, 803–805
 multimedia compression standards, 801
 video compression algorithm, 803–805
- MPDU field, IEEE 802.11b, 548
- Multi_Exit_Disc attribute, BGP, 620, 622
- Multicast Address, IGMP, 613
- Multicast addressing, 564, 593, 605
- Multicast transmission, RSVP, 635, 636
- Multicasting, 604, 605–614
 applications of, 605
 broadcast strategy, 606–607
 defined, 604
 Internet Group Management Protocol (IGMP), 610–614
 multicast strategy, 607–608
 multiple unicast strategy, 607
 requirements for, 608–610
- Multilevel binary encoding technique, 146–147
 bipolar-AMI scheme, 146
 digital data, digital signal encoding, 146–147
 pseudoternary, 146
- Multilevel phase-shift keying (MPSK), 157–158
- Multimedia, 48–53, 700, 799–833
 applications, 50–51
 audio, 50, 801–802
 communications/networking, 52
 compression, 52, 800–808
 defined, 49
 elastic traffic, 51–52
 image, 50
 inelastic traffic, 51–52
 Internet applications, 700, 799–833
 introduction to, 48–49
 media types, 49–50
 protocols, 52
 quality of service (QoS), 52–53
 real-time traffic, 808–811
 Real-Time Transport Protocol (RTP), 800, 820–831
 recommended reading and Web sites, 831–832
 Session Description Protocol (SDP), 811, 820
 Session Initiation Protocol (SIP), 800, 811–820
 technologies, 52–53
 text, 49–50
 use of, 700, 800
 video, 50, 803–808
 voice over IP (VoIP), 811
- Multipart type, MIME, 753, 755
- Multipath interference, 132–133
- Multipath resistance, CDMA, 430
- Multiple frequency shift keying (MFSK), 153–154, 279–282
 FHSS using, 279–282
 signal encoding scheme, 153–154
- Multiplexing, 239–273, 276, 287–290, 545, 564–565, 658–659
 asymmetrical digital subscriber line (ADSL), 265–268
 code division (CMA), 276
 code division multiple access (CDMA), 276, 287–290
 defined, 240
 dense wavelength division (DWDM), 247–248
 discrete multitone (DMT), 267–268
 frequency division (FDM), 240, 241, 242–248
 high data rate digital subscriber line (HDSL), 268–269
 introduction to, 240–241
 network service, 658–659
- orthogonal frequency division (OFDM), 545
- protocol function, 564–565
- recommended reading and Web sites, 269–270
- single line digital subscriber line (SDSL), 269
- statistical time division, 240, 241, 258–265
- Synchronous Digital Hierarchy (SDH), 255–258
- Synchronous Optical Network (SONET), 255–258
- synchronous time division, 240, 248–258
- time division (TDM), 240, 241, 248–258, 258–265
- very high data rate digital subscriber line (VDSL), 268–269
- wavelength division (WDM), 247–248
 xDSL, 268–269
- Multipoint transmission medium, 67
- Multi-Purpose Internet Mail Extension Protocol (MIME), 744, 752–760
 audio type, 757
 content types, 753–757
 image type, 756
 introduction to, 744, 752
 message type, 755–756
 multipart type, 753, 755
 overview of, 753
 text type, 753
 transfer encodings, 757–760
 video type, 756
- Multirate, 3G cellular systems, 439–440
- ## N
- Near-far problems, CDMA, 430
- Neighbor acquisition, BGP, 618
- Neighbor reachability, BGP, 618
- Network access layer, TCP/IP, 35
- Network access point (NAP), defined, 28–29
- Network classes, IP addresses, 579–580
- Network interface, circuit switching, 305
- Network jitter, 646
- Network Layer Reachability Information (NLRI) field, BGP, 620, 622
- Network management, *see* Simple Network Management Protocol (SNMP)
- Network reachability, BGP, 619
- Network response, frame relays, 393
- Network security, 699, 701–742
 active attacks, 702, 704–705
 Advanced Encryption Standard (AES), 707–710
 confidentiality, 703, 705–713
 Data Encryption Standard (DEA), 707
 defined, 703
 digital signatures, 722–723
 hash functions, 716–720
 introduction to, 699, 7102–703
 IP (IPSec), 732–736
 message authentication, 713–720
 passive attacks, 702, 704
 public-key encryption, 702, 720–727
 recommended reading and Web sites, 739–740

- Network security (*cont.*)
 - requirements, 703
 - RSA algorithm, 723–726
 - Secure Sockets Layer (SSL), 727–732
 - symmetric encryption, 702, 705–713, 714
 - Wi-Fi Protected Access (WPA), 550, 737–739
 - Network service, 28–29, 45, 657–674
 - access point (NSAP), 45
 - addressing, 657–658
 - connection establishment, 663
 - connection termination, 663, 673–674
 - duplicate detection, 667–668
 - failure recovery, 674
 - flow control, 659–663, 668–673
 - multiplexing, 658–659
 - ordered delivery, 666
 - provider (NSP), 28–29
 - reliable sequencing, 657–665
 - retransmission strategy, 666–667
 - unreliable, 665–674
 - Networking, 12–16, 29–31, 526
 - ad hoc, 526
 - capacity requirements, 14
 - configuration, example of, 29–31
 - corporate wide area networking (WAN), 15
 - data communications and, 12–16
 - digital electronics, 15–16
 - high-speed LANs, emergence of, 14–15
 - services, 12–13
 - trends, 12–13
 - Networks, 14–15, 22–24, 25, 295–443, 444–553, 596–599
 - ARAPNET, 362–367
 - asynchronous transfer mode (ATM), 23–24, 296, 328–350
 - cellular wireless, 296, 413–443
 - circuit switching, 23, 295, 301–304
 - congestion control, 296, 377–412
 - data, 377–412
 - frame relay, 23, 319–323
 - high-speed LANs, 14–15, 445, 482–521
 - integration, 22
 - Internet connection, 25
 - introduction to, 22
 - local area (LAN), 22, 24, 444–553
 - packet switching, 23, 295, 298, 309–323, 352–372
 - routing, 296, 351–376
 - switched, 297–327, 351–376
 - virtual private (VPN), 596–599
 - wide area (WAN), 22–23, 295–443
 - wireless, 24, 296, 413–443, 445, 522–553
 - Next generation IP, motivation and details of, 557, 586–588
 - Next Header field, IPv6, 590
 - Next_Hop attribute, BGP, 620, 621, 622
 - Nodes, 299, 300, 315–316, 502, 527
 - defined, 299
 - delay, circuit and packet switching, 315–316
 - Fibre Channel network, 502
 - switched communication network, 300
 - wireless LAN requirements, 527
 - Noise, 89–91, 92, 93–94, 144, 163–164
 - channel capacity, 92, 93–94
 - crosstalk, 90
 - immunity, 144
 - impulse, 90–91
 - intermodulation, 90
 - quantizing, 163–164
 - Shannon capacity formula, 93–94
 - signal-to-noise ratio (SNR), 93–94
 - thermal, 89
 - transmission impairment, 89–91
 - white, 89
 - Nomadic access, wireless LANs, 525–526
 - Nonconfirmed service, defined, 48
 - Nonpersistent CSMA algorithm, 486
 - Non-real-time service, 345, 346–348
 - Non-real-time variable bit rate (nrt-VBR), 345, 346
 - Nonreturn to Zero (NRZ), 144–145, 508–510
 - coding scheme, 508
 - conversion, NRZI to NRZ, 510
 - differential encoding, 144–145
 - digital signal encoding, 144–145, 508–510
 - 4B/5B code, 508–510
 - high-speed LANs, 508–510
 - Nonreturn to Zero Invert (NRZI), 144, 508–509
 - Nonreturn to Zero-Level (NRZL), 144
 - Normal response mode (NRM), 222
 - Notification Message, BGP, 621
 - Nyquist bandwidth, 92–93
- O**
- Offset, IP fragmentation and reassembly, 574, 575
 - 1-persistent protocol, CSMA, 487
 - Open Shortest Path First (OSPF) Protocol, 623–625, 626, 627
 - autonomous system (AS), 623–625
 - directed graph, 632, 625
 - internetwork routing, 623–625, 626, 627
 - Open Systems Interconnection (OSI) model, 42–44, 44–48
 - addressing, 45
 - confirm primitive, 47
 - confirmed service, 48
 - indication primitive, 47
 - introduction to, 42–44
 - network service access point (NSAP), 45
 - nonconfirmed service, 48
 - parameters, 46–48
 - primitives, 46–48
 - protocol specifications, 45
 - request primitive, 47
 - response primitive, 47
 - service access point (SAP), 45
 - service definitions, 45
 - standardization within, 44–48
 - Optical fiber, 20, 112–116, 456
 - applications of, 113–114
 - cladding, 113
 - core, 113
 - description of, 112–113
 - fiber optic transmission, 20
 - graded-index multimode, 115
 - jacket, 113
 - LAN topology, 456
 - single-mode, 115
 - step-index multimode, 114–115
 - total internal reflection, 114
 - transmission characteristics of, 114–116
 - Option data, IP protocol, 577
 - Options field, 579, 679
 - IP protocol, 579
 - TCP, 679
 - Ordered delivery, 561, 666
 - Origin attribute, BGP, 620
 - Origin server, HTTP, 786
 - Orthogonal frequency division multiplexing (OFDM), 545
 - Orthogonal property, CDMA, 288
 - OSI, *see* Open Systems Interconnection (OSI) model
 - OSPF, *see* Open Shortest Path First (OSPF) Protocol
- P**
- p*-persistent protocol, CSMA, 487–488
 - Packet discard, ISA, 629
 - Packet loss, inelastic traffic, 52, 628
 - Packet switching, 23, 295, 298, 309–317, 317–319, 319–323, 352–362, 362–367, 367–372, 387–388
 - ARAPNET, 362–367
 - circuit switching, comparison to, 315–317
 - congestion control, 387–388
 - datagram approach, 310, 311
 - defined, 298
 - networks, 23, 352–362, 362–367, 367–372, 387–388
 - node delay, 315–316
 - packet size, 313–315
 - principles of, 309–317
 - propagation delay, 315–316
 - routing, 352–362, 362–367, 367–372
 - switching technique, 310/313
 - transmission time, 315–316
 - use of, 23, 295, 298
 - virtual circuit approach, 310, 321–313
 - X.25 interfacing standard, 317–319
 - Packets, 25, 57–59, 313–315, 384–385, 630–631, 810, 827–831. *See also* Datagrams
 - application-defined, 828, 831
 - choke, 384–385
 - classifier and route selection, ISA, 630–631
 - continuous data source, 811
 - Goodbye (BYE), 828, 831
 - IP datagrams, 25
 - ISA forwarding functions, 630–631
 - on/off source, 810
 - packet scheduler, ISA, 631
 - real-time traffic, 811
 - Receiver Report (RR), 828, 830
 - RTP Control Protocol (RTCP), 827–831
 - Sender Report (SR), 827–830
 - size of, 313–315, 810
 - Source Description (SDES), 828, 830
 - TFTP, 57–59
 - Pad, IEEE 802.3, 492
 - Padding, 579, 713, 824
 - IP protocol, 579
 - RTP header, 824
 - traffic, 713
 - Paging, cellular systems, 421, 433
 - Parabolic reflective antenna, 117–118
 - Parameter problem message, ICMP, 584

- Parameters header, ICMP, 583
- Parity check, 188–189
- Passive attacks, 702, 704. *See also* Encryption
- Path Attributes field, BGP, 620–621
- Path-vector routing, 617–618
- Payload, 337, 590, 825–826
 - ATM, Type (PT) field, 337
 - length field, IPv6, 590
 - RTP, Type, 825–826
- PCF, *see* Point coordination function (PCF)
- PCM, *see* Pulse code modulation (PCM)
- PDU, *see* Protocol data unit
- Peak amplitude, 68
- Peak cell rate (PCR), 402–403
- Peer layers, protocol, 34
- Performance metrics, 646–649
 - active techniques, 647
 - IP Performance Metrics (IPPM) Working Group, 646–649
 - passive techniques, 647
 - types of, 647
- Per-hop behavior (PHB), 642–645
 - assured forwarding (AF), 644–645
 - defined, 642
 - expedited forwarding (EF), 643–644
 - traffic conditioning functions, 642–643
- Period, defined, 69
- Periodic signal, 68, 836–837, 838
 - dc component, 836
 - defined, 68
 - Fourier series representation of, 836–837, 838
 - fundamental frequency, 836
 - harmonics, 836
- Permanent key, defined, 713
- Persist timer, flow control, 669
- Personal communication networks (PCNs), 437
- Personal communication services (PCSs), 437
- Personal computer, LANs, 448
- Phase, defined, 69
- Phase modulation (PM), 171–174
- Phase shift keying (PSK), 139, 154–158, 277–278, 282–284
 - binary (BPSK), 277–278, 282–284
 - defined, 139
 - digital data, analog signal encoding, 154–158
 - DSSS using, 282–284
 - FHSS using, 277–278
 - four-level, 155–157
 - multilevel (MPSK), 157–158
 - signal encoding schemes, 154–158
 - two-level (binary), 154–155
- PHB, *see* Per-hop behavior (PHB)
- Physical layer, 35, 340–343, 343–345, 457, 496–497, 543–549
 - cell-based, ATM, 340–343
 - channel structure, IEEE 802.11a, 545
 - coding, IEEE 802.11a, 545–546
 - complementary code keying (CCK), 547
 - direct sequence spread spectrum (DSSS), 543, 544
 - frame structure, 546, 548
 - frequency-hopping spread spectrum (FHSS), 543, 544–545
- Gigabit Ethernet, 496–497
- IEEE 802, 457
 - IEEE 802.11, 543–549
 - IEEE 802.11a, 543, 545–547
 - IEEE 802.11b, 547–548
 - IEEE 802.11g, 548–549
 - infrared, 544, 545
 - modulation, 545–546, 547
 - orthogonal frequency division multiplexing (OFDM), 545
 - packet binary convolution coding (PBCC), 548
 - PLCP Preamble field, 546, 548
 - pulse position modulation (PPM), 545
 - SDH-based, ATM, 343–345
 - TCP/IP, 35
 - Universal Networking Information Infrastructure (UNNI), 545
- Piggybacking, 214
- Pilot channels, 433
- Plaintext, defined, 705
- PLCP header, IEEE 802.11b, 548
- PLCP Preamble field, IEEE 802.11a and b, 546, 548
- Point coordination function (PCF), 536, 539, 540–541
 - DCF access, 540–541
 - interframe space (PIFS), 539
 - Mac algorithm, 536
- Point of presence (POP), defined, 26, 27–28
- Point-to-point transmission medium, 67, 104, 106
- Polar signaling, 141
- Policing, 405, 407
 - GFR, 407
 - traffic, 405
- Poll response, IEEE 802.11 MAC, 540
- Polynomial division, 192–193
- Port, 37, 658, 676
 - destination, 37, 676
 - network service, 658
 - TCP addresses, 37, 676
- Portal, 802.11 model, 532
- Postamble bit pattern, 185
- Power Save-Poll (PS-Poll), IEEE 802.11 MAC, 542
- Power spectral density (PSD), 837, 839–840
- Power workgroups, 15
- Preamble, IEEE 802.3, 490
- Preamble bit pattern, 185
- Prediction, video compression, 805–806
- Primary station, HDLQ, 222
- Priority, protocol transmission service, 565
- Privacy, 86, 430, 550
 - CDMA, 430
 - digital transmission, 86
 - IEEE 802.11, 550
 - Wired Equivalent Privacy (WEP) algorithm, 550
- Private branch exchange (PBX), 305
- Propagation delay, 315–316, 514–517
 - circuit and packet switching, 315–316
 - high-speed LANs, 514–517
- Protocol, 32–61, 207–238, 321–322, 329–330, 457–465, 487–488, 503, 554–555, 556–602, 603–654, 655–698, 728–732, 744, 745–752, 752–760, 760–770, 774, 784–798, 800, 811–820, 820–831
 - Address Resolution (ARP), 585–586
 - addressing, 562–564
 - Alert, SSL, 730
 - architecture, 32–61, 321–322, 329–330, 457–465, 503, 821–822
 - ATM, 329–330
 - basic functions of, 558–566
 - Border Gateway (BGP), 618–623
 - Change Cipher Spec, SSL, 730
 - connection control, 559–561
 - control, PDU information, 558
 - control plane, 321
 - CSMA, 487–488
 - data link control, 207–238
 - data transfer, RTP, 822–825
 - data units (PDU), 460, 558, 768–769
 - defined, 34
 - encapsulation, 558
 - error control, 216–221, 561–562
 - exterior router (ERP), 616
 - Fibre Channel, 503
 - File Transfer (FTP), 41
 - flow control, 209–216, 561
 - fragmentation, 558–559
 - frame relay, 321–322
 - Handshake, SSL, 730–732
 - high-level data link control (HDLC), 222–228
 - Hypertext Transfer (HTTP), 700, 774, 784–798
 - IEEE 802 refiner model, 457–460
 - interfaces, 41–42
 - interior router (IRP), 615–616
 - Internet (IP), 35, 554–555, 556–602
 - Internet-based applications, 48
 - Internet Control Message (ICMP), 582–585
 - internetwork operation, 554–555, 603–654
 - internetworking, principles of, 566–569
 - introduction to, 33, 208–209
 - LAN, 457–465
 - logical link control (LLC), 458, 460–463
 - medium access control (MAC), 458, 463–465
 - multimedia, 52
 - multiplexing, 564–565
 - Multi-Purpose Internet Mail Extension (MIME), 744, 752–760
 - need for, 33–34
 - 1-persistent, 487
 - Open Shortest Path First (OSPF), 623–625, 626, 627
 - Open Systems Interconnection (OSI) model, 42–44, 44–48
 - ordered delivery, 561
 - peer layers, 34
 - p*-persistent protocol, 487–488
 - Real-Time Transport (RTP), 800, 820–831
 - recommended reading and Web site, 53–54
 - Record, SSL 728–730
 - routing, 604, 614–625, 626
 - RTP Control Protocol (RTCP), 821, 826–831
 - semantics, 34
 - Session Description (SDP), 800, 811, 820
 - Session Initiation (SIP), 800, 811–820
 - Simple Mail Transfer (SMTP), 41, 48, 744, 745–752

- Protocol (*cont.*)
 Simple Network Management (SNMP), 744, 760–770
 SNMPv2 operation, 767–769
 SSL, 728–732
 standardization within, 44–48
 syntax, 34
 TCP/IP, 34–42
 timing, 34
 Transmission Control (TCP), 36, 656, 647–693
 transmission services, 565
 transport, 556, 655–698
 Trivial File Transfer (TFTP), 57–61
 User Datagram (UDP), 38–39, 41, 656, 693–694, 762–763
 user plane, 321–322
- Protocol data unit (PDU), 460, 558, 768–769
 encapsulation, 558
 logical link control (LLC), 460
 MPDU field, IEEE 802.11b, 548
 SNMPv2, 768–769
- Proxy, HTTP, 787
 Pseudonoise (PN), 277
 Pseudorandom numbers, 276
 PSK, *see* Phase shift keying (PSK)
 Public-key encryption, 702, 720–727
 certificate, 726–727
 characteristics of, 722
 digital signatures, 722–723
 key management, 726–727
 requirements, 722
 RSA algorithm, 723–726
 use of, 720–721
- Public switched telephone network (PSTN), 12
- Public telecommunications network, 302–303
- Pulse amplitude modulation (PAM), 164, 801
- Pulse code modulation (PCM), 162–165, 254, 801
 analog data, digital signal encoding, 140, 162–168
 audio compression, 801
 quantizing noise (error), 163–164
 sampling theorem, 162
 TDM digital carrier systems, 254
- Pulse position modulation (PPM), 545
- Pulse stuffing, 252–253
- Q**
- Quadrature amplitude modulation (QAM), 161, 267
- Quadrature phase-shift keying (QPSK), 155–157
- Quality of service (QoS), 12, 52–53, 334, 387, 406–408, 565, 625–629, 826
 congestion, traffic management, 387
 eligibility test, GFR, (408)
 Integrated Services Architecture (ISA), 625–636
 multimedia, 52–53
 protocol transmission service, 565
 RTP Control Protocol (RTCP), 826
 transport, 628–629
 trend of, 12
 VCC, 334
 VPC, 334
- Quantization, video compression, 804
 Quantizing noise (error), 163–164
- Querier's querier interval code (QQIC), IGMP, 611
- Querier's robustness variable (QRV), IGMP, 611
- Question section, DNS messages, 783, 784
- Queuing, 629, 633–636, 640–641
 congestion control, DS, 640–641
 DS discipline, 640
 first-in-first-out (FIFO), 633–634
 ISA discipline, 629, 633–636
 service, DS, 640
 weighted fair (WFQ), 634
- Quoted-printable transfer encoding, 757–758
- R**
- Radio, 117, 124, 125, 128–129, 129–133, 422–424
 applications of, 124
 atmospheric absorption, 132
 broadcast, 124
 frequency ranges, 117, 124
 ground wave propagation, 125
 line of sight (LOS), 125–129, 129–133
 mobile propagation effects, 422–424
 range, 117
 refraction of waves, 133
 scattering, 132
 sky wave propagation, 125
 transmission characteristics of, 124
- RAKE receiver, CDMA cellular system, 431
- Random access, video compression, 804
- Random routing, 359–360
- Rate guarantees, GFR, 406–407
- RCPT command, SMTP, 750
- Read request (RRQ) packet, 58
- Real-time service, 345–346
- Real-time traffic, 808–811
 applications, hard versus soft, 811
 characteristics of, 809–810
 delay jitter, 809–810
 requirements for, 810–811
- Real-Time Transport Protocol (RTP), 800, 820–831
 application-level framing, 821–822
 Control Protocol (RTCP), 821, 826–831
 data transfer protocol, 822–826
 integrated layer processing, 822
 protocol architecture, 821–822
 use of, 800, 820–821
- Real-time variable bit rate (rt-VBR), 345, 346
- Receive ready (RR), 218, 219, 226
 acknowledgement, 218, 219
 frame, HDLC, 226
- Receiver, 17, 104, 541, 747
 address, IEEE 802.11 MAC, 541
 defined, 17
 number of, 104
 SMTP, 747
- Receiver Report (RR), RTCP, 828, 830
- Record Protocol, 728–730
- Record Type field, IGMP
- Recursive technique, DNS name resolution, 782
- Redirect message, ICMP, 584
- Reflection, mobile communication, 424
- Refraction, 128, 133
 index of, 128
 line-of-sight (LOS) and, 128, 133
 radio waves, 133
- Reject (REJ), 218, 219, 226
 damaged, 219
 frame, HDLC, 226
 go-back-N technique, 218, 219
 Release of message contents, 704
- Remote mobile subscriber, calls to/from, 422
- Repeaters, ring topology, 453
- Replay, network attack, 704
- Replies, SMTP, 748–749
- Request messages, 791–793, 817–819
 headers, 792–793, 818–819
 HTTP, 791–793
 method, 719–792, 817–818
 SIP, 817–819
- Request primitive, 47
- Request to Send (RTS), IEEE 802.11 MAC, 542
- Reservation protocol, ISA, 630
- Reservations, 387, 464
 congestion traffic management, 387
 MAC traffic approach, 464
- Reserved header, TCP, 677
- Resource management, 400–402
- Resource records (RRs), DNS, 777–778
- Resource ReSerVation Protocol (RSVP), 604, 635–636
 characteristics of, 636
 ISA functionality, 635–636
 multicast transmission, 635, 636
 soft state, 636
 unicast transmission, 635, 636
 use of, 604
- Response messages, 793–794, 817, 819–820
 code, SIP, 817
 headers, 794, 819–820
 HTTP, 793–794
 SIP, 819–820
 status codes, HTTP, 793
- Response primitive, 47
- Retransmission timer management, 683–690
 exponential average, 684–686
 exponential RTO backoff, 688–689
 Jacobson's algorithm, 686–688
 Karn's algorithm, 689–690
 retransmission timer (RTO), 686
 round-trip time (RTT), 684
 RTT variance estimation, 686–688
 simple average, 684
 TCP congestion control, 683–690
- Retransmission, 216, 666–667, 683–689
 frames, 216
 segments, 666–667
 TCP retransmission timer management, 683–690
 timer (RTO), 667, 686
 unreliable network service, 666–667
- Retransmit policy, TCP, 681–682
- Retransmit-SYN timer, 670
- Reuse frequency, 416–417
- Reverse control channels (RCCs), 428–429
- RFC 822 format, SMTP, 751–752
- Ring topology, 447, 453, 455
- Roaming, wireless LANs, 528
- Root name servers, DNS, 781
- Round robin, MAC traffic approach, 464
- Round-trip propagation time, traffic and congestion control, 399
- Round-trip time (RTT), 684
- Route recording, IP protocol, 577

- Routers, 25, 567
 - defined, 25
 - internetworking, 567
- Routing, 162, 296, 351–376, 468–471, 573, 577, 604, 614–625, 626, 627, 629, 630
 - adaptive, 360–362
 - algorithms, 362–367, 367–372, 629
 - approaches to, 616–618
 - ARAPNET, 362–367
 - bridges, LAN, 468–471
 - characteristics of, 353–356
 - decision time and place, 355
 - defined, 18
 - distance-vector, 616
 - fixed, 356–357, 468–471
 - flooding, 357–359
 - information update timing, 356
 - internetwork operation, 604, 614–625, 626, 627
 - introduction to, 296, 352
 - IP design, 573
 - ISA functions, 629, 630
 - least-cost algorithms, 367–372
 - link-state, 616–617
 - network information source, 355–356
 - packet-switching networks, 352–362, 362–367, 367–372
 - path-vector, 617–618
 - performance criteria, 353–355
 - protocols, 604, 614–625, 626, 627, 630
 - random, 359–360
 - recommended reading, 372–373
 - source, 470, 577
 - spanning tree algorithm, 470
 - strategies, 356–362
- Routing header, IPv6, 588, 595
- Routing protocols, 604, 614–625, 626, 627
 - autonomous system (AS), 614–616, 623–625
 - Border Gateway Protocol (BGP), 618–623
 - distance-vector routing, 616
 - exterior (ERP), 616
 - interior (IRP), 615–616
 - link-state routing, 616–617
 - Open Shortest Path First (OSPF) Protocol, 623–625, 626, 627
 - path-vector routing, 617–618
 - use of, 604, 614
- RSA public-key encryption algorithm, 723–726
- RSVP, *see* Resource ReSerVation Protocol (RSVP)
- RTP Control Protocol (RTCP), 821, 826–831
 - application-defined packet, 828, 831
 - congestion control, RTCP Goodbye (BYE), 828, 831
 - identification, 826
 - packet types, 827–831
 - Quality of service (QoS), 826
 - Receiver Report (RR), 828, 830
 - Sender Report (SR), 827–830
 - session control, 827
 - session size, 826–827
 - Source Description (SDES), 828, 830
- RTP, *see* Real-Time Transport Protocol (RTP)
- RTT variance estimation, 686–688
- Run-length encoding, video
 - compression, 804
 - duplicate detection, 667–668
 - failure recovery, 674
 - flow control, 659–663, 668–673
 - IP datagram, 38
 - ordered delivery, 666
 - retransmission strategy, 666–667
 - sequence number, 37, 661
 - TCP, 37
 - unreliable network service, 665–674
 - window, 661
- Selective cell discard, 405
- Selective fading, 426
- Selective-reject, 221, 226, 237
 - ARQ, 221, 237
 - frame, HDLC, 226
- Self-jamming, CDMA, 430
- Semantics, 34, 61
 - TCP/IP, 34
 - TFTP, 61
- Semipermanent VCC and VPC, 334, 335
- Send policy, TCP, 681
- Sender, SMTP, 746–747
- Sender Report (SR), RTCP, 827–830
- Sequence Control, IEEE 802.11 MAC, 541
- Sequence number, TCP, 37, 676, 679
- Server, SIP, 812
- Server hierarchy, DNS, 779–782
 - root name servers, 781
 - zone, 779–781
- Service access point (SAP), 45
- Service level agreements (SLA), 645–646
- Service parameters, 46–48, 576–577, 677
 - IP, 576–577
 - OSI model, 46–48
 - TCP, 677
- Service primitives, 46–48, 576–577, 675–676
 - IP, 576–577
 - request, TCP, 675
 - response, TCP, 676
 - types of, OSI model, 46–48
- Service provider (ISP), defined, 26, 27–28
- Service set ID (SSID), IEEE 802.11 MAC, 541
- Services, 12–13, 345–348, 460–461, 532, 533–535, 550, 565, 576–577, 631–633, 675–676
 - access and privacy, IEEE 802.11, 550
 - acknowledged connectionless, 460, 461
 - association-related, 535
 - ATM, 345–348
 - available bit rate (ABR), 345, 347
 - basic service set (BSS), 532
 - best-effort, 347
 - connection-mode, 460, 461
 - constant bit rate (CBR), 345, 346
 - controlled load, ISA, 633
 - distribution system (DS), 532, 534–535
 - extended service set (ESS), 533
 - guaranteed, ISA, 632–633
 - guaranteed frame rate (GFR), 345, 348
 - IEEE 802.11 model, 533–535, 550
 - independent basic service set (IBSS), 532
 - integration, 534–535
 - Internet protocol (IP), 576–577
 - ISA, 631–633

- Services (*cont.*)
 - LLC, 460–461
 - MAC service data units (MSDU)
 - delivery, 534–535
 - message distribution using DS, 534–535
 - networking, 12–13
 - non-real-time, 345, 346–348
 - range of, 12–13
 - real-time, 345–346
 - TCP, 675–676
 - traffic specification (Tspec), ISA, 631–632
 - transmission, protocol, 565
 - unacknowledged connectionless, 460–461
 - unspecified bit rate (UBR), 345, 347
 - variable bit rates (VBRs), 345, 346
- Session control, RTPC, 827
- Session Description Protocol (SDP), 800, 811, 820
- Session Initiation Protocol (SIP), 800, 811–820
 - client, 812
 - components, 812–814
 - messages, 817
 - multimedia support of, 811–820
 - operation, examples of, 814–817, 818
 - requests, 817–819
 - responses, 819–820
 - server, 812
 - Session Description Protocol (SDP), 800, 811, 820
 - Uniform Resource Identifier (URI), 814
 - use of, 800, 811
 - voice over IP (VoIP), 811
- Session key, defined, 712
- Session size, RTPC, 826–827
- Shannon capacity formula, 93–94
- Shaper, DS traffic conditioning
 - function, 642–643
- Shielded twisted pair (STP), 109, 110–111
- Signal interference and noise
 - reduction, 144
- Signal spectrum, 143
- Signal-to-noise ratio (SNR), 93–94
- Signaling, 78, 139, 141, 254, 335, 385–386
 - analog, 139
 - bit, 254
 - control. ATM, 335
 - data rate, 141
 - defined, 78
 - digital, 139
 - explicit congestion, 385–386
 - implicit congestion, 385
 - meta-signaling channel, 335
 - modulation rate, 141
 - polar, 141
 - unipolar, 141
 - user-to-network signaling virtual channel, 335
 - user-to-user signaling virtual channel, 335
- Signals, 17, 67–72, 78, 80–86, 86–91, 99–101, 139, 140, 243–244, 244–246, 255, 279, 422–424, 424–427, 836–840. *See also* Bandwidth; Encoding
 - analog, 67, 80–86
 - analog transmission, 84–85
 - aperiodic, 68, 837, 839–840
 - attenuation, 99
 - bandwidths, 837, 839–840
 - baseband, 140
 - carrier, 139
 - chipping, 279
 - data, 78, 83–84
 - decibels and, 99–101
 - defined, 78
 - digital, 68, 80–86
 - digital transmission, 85–86
 - fading, 422, 424–427
 - Fourier series representation of, 836–837, 838
 - Fourier transform representation of, 837, 839–840
 - frequency, 68–69, 836
 - frequency domain, 67, 70–72
 - generation, 17
 - hierarchy, SONE/SDH, 255
 - mobile radio propagation effects, 422–424
 - peak amplitude, 68
 - period, 69
 - periodic, 68, 836–837, 838
 - phase, 69
 - power spectral density (PSD), 837, 839–840
 - sinusoid function, 69
 - strength, 99–101, 422
 - time domain, 67–70
 - transmission impairment, 86–91
 - TV, FDM, 243–244
 - voiceband, FDM, 244–246
 - wavelength, 70
- Simple average, TCP congestion control, 684
- Simple Mail Transfer Protocol (SMTP), 41, 48, 744, 745–752
 - commands, 748
 - connection closing, 751
 - connection setup, 749–750
 - envelope, 745
 - Internet-based application, 48
 - mail transfer, 750–750
 - operation of, 745–747
 - overview of, 747–749
 - protocol, 747
 - receiver, 747
 - replies, 748–749
 - RFC 822 format, 751–752
 - sender, 746–747
 - use of, 41, 744
- Simple Network Management Protocol (SNMP), 744, 760–770
 - architecture, 762–764
 - concepts of, 761–762
 - defined, 761
 - management agent, 761–762
 - management information base (MIB), 762, 765
 - management station, 761
 - network management, defined, 18
 - network management systems, 760–761
 - recommended reading and Web site, 770–771
 - traps, 764
 - UDP and, 762–763
 - use of, 744, 760–761
 - version 1, 761–764
 - version 3 (SNMPv3), 769–770
 - version 2 (SNMPv2), 764–769
- Simplex, RSVP, 636
- Simplex transmission, 67
- Single-bit error, 186
- Single line digital subscriber line (SDSL), 269
- Singleton metric, 647
- Sinusoid function, 69
- SIP. *see* Session Initiation Protocol (SIP)
- 64B/66B encoding, 513–514
- Sky wave propagation, 125, 127
- Sliding-window flow control, 212–216, 234–236
 - data link control protocol, 212–216
 - performance issues, 234–236
- Slow fading, 426
- Slow start, TCP congestion control, 690–691
- SMTP. *see* Simple Mail Transfer Protocol (SMTP)
- SNMP. *see* Simple Network Management Protocol (SNMP)
- SNMPv3, 769–770
- SNMPv2, 764–769
 - data types, 767
 - elements of, 765–767
 - protocol data units (PDUs), 768–769
 - protocol operation, 767–769
 - structure of management information (SMI), 765, 767
 - use of, 764
- SNR. *see* Signal-to-noise ratio (SNR)
- Socket, network service transport, 658
- Soft state, RSVP, 636
- Softswitch architecture, 307–309
- Source, defined, 16
- Source address, 464, 492, 541, 577, 590
 - IEEE 802.11 MAC, 541
 - IEEE 802.3, (SA), 492
 - IGMP, 613
 - IP protocol, 577, 579
 - IPv6, 590
 - MAC, 464
- Source Description (SDES), RTPC, 828, 830
- Source Input Format (SIF), 803
- Source quench message, ICMP, 584
- Source routing, 470, 577
 - IEEE 802, 470
 - IP protocol, 577
- Sources, number of, IGMP, 613
- Space diversity, 427
- Space division switching, 305–307
- Spanning tree, 470, 471–473
 - address learning, 471–472
 - algorithm, 470, 472–473
 - approach, 471–473
 - forwarding database, 471
 - frame forwarding, 471
- Spectral allocation, AMPS, 427–428
- Spectrum, defined, 72
- Spread spectrum, 274–294
 - code division multiple access (CDMA), 275, 276, 287–290
 - concept of, 276
 - defined, 275
 - direct sequence (DSSS), 275, 282–286, 289–290
 - frequency-hopping (FHSS), 275, 277–282
 - introduction to, 275
 - recommended reading and Web site, 290
- Spread spectrum LANs, 528, 530
 - configuration of, 530
 - defined, 528
 - FCC licensing, 528, 530
 - transmission issues, 530

- Star topology, 447, 454
- Start Frame Delimiter (SFD), IEEE 802.3, 490
- Start-of-frame delimiter, IEEE 802.11b, 548
- Stations, 222, 299
 - HDLQ, 222
 - network devices, 299
- Statistical metric, 647
- Statistical multiplexing, VPC, 402
- Statistical time division multiplexing, 240, 241, 258–265
 - cable modem, 264–265
 - characteristics of, 258–260
 - defined, 240, 241
 - frame formats, 259
 - performance of, 260–264
- Status codes, HTTP, 793
- Stop-and-wait, 210–212, 217, 232–234, 237
 - acknowledgement frame, 215
 - ARQ, 217, 237
 - data frame, 214–215
 - data link control protocol, 210–212
 - flow control, 210–212, 232–234
 - performance issues, 232–234, 237
 - piggybacking, 214
 - transmission time, 211–212, 232–234
- Stop element, asynchronous transmission, 183
- Storage area network (SAN), 449
- Store-and-forward switch, 476
- Stream delimiter, start and end of, NRZI, 510
- Stream identification, IP protocol, 577
- Structure of management information (SMI), SNMPv2, 765, 767
- STS-1 (Synchronous Transport level 1), *see* Synchronous Optical Network (SONET)
- Subcarrier, defined, 243
- Subnets and subnet masks, IP addresses, 580–582
- Subnetworks, 36, 477–478, 566
 - address, 38
 - internetworking, 566
 - LAN switches and, 477–478
 - TCP/IP, 36
- Subscriber line, 302
- Subscribers, public
 - telecommunications network, 302
- Supervisory frames (S-frames), 224
- Sustainable cell rate (SCR), 402–403
- Switched communications networks, 296, 297–327, 351–376
 - ARAPNET, 362–367
 - circuit switching, 295, 298, 301–304, 304–309, 315–317
 - example of, 299–300
 - frame relay, 319–323
 - least-cost algorithms, 367–372
 - nodes, 299, 300
 - packet switching, 295, 298, 309–317, 317–319, 319–323, 352–362, 362–367, 367–372
 - recommended reading and Web sites, 324
 - routing, 296, 351–376
 - X.25 interfacing standard, 317–319
- Switched VCC and VPC, 334
- Switches, 447, 473–478
 - broadcast storm, 477
 - cut-through, 476
 - hubs and, 474–475
 - LAN use of, 447, 473–478
 - layer 3, 476–478
 - layer 2, 474–475
 - store-and-forward, 476
 - subnetworks, 477
- Symmetric encryption, 702, 705–713, 714
 - Advanced Encryption Standard (AES), 707–710
 - brute force attack, 706
 - ciphertext, 706
 - cryptanalysis, 706
 - Data Encryption Standard (DES), 707
 - decryption algorithm, 706
 - encryption algorithms, 705, 707–710
 - key distribution, 711–713
 - location of devices, 710–711
 - message authentication using, 714
 - plaintext, 705
 - requirements for, 706
 - secret key, 705
 - traffic padding, 713
- Synchronization, 17–18, 181, 443
 - channels, 433
 - digital data, 181
 - signals, 17–18
- Synchronization source (SSRC) identifier, 825
- Synchronous Digital Hierarchy (SDH), 255–258
 - frame formats, 256–258
 - ITU-T designations, 255
 - signal hierarchy, 255
- Synchronous Optical Network (SONET), 255–258
 - frame formats, 256–258
 - overhead bits, 257
 - overhead octets, 256
 - signal hierarchy, 255
 - STS-1 (Synchronous Transport level 1), 255–258
- Synchronous time division multiplexing, 240, 248–258
 - characteristics of, 248–250
 - defined, 240
 - digital carrier systems, 253–255
- Synchronous Digital Hierarchy (SDH), 255–258
- Synchronous Optical Network (SONET), 255–258
 - TDM link control, 250–253
- Synchronous transmission, 181, 182–183, 185–186
 - defined, 181
 - frame, 185
 - postamble bit pattern, 185
 - preamble bit pattern, 185
- Syntax, 34, 61
 - TCP/IP, 34
 - TFTP, 61
- T**
- Tagging, GFR, 407
- TCP, *see* Transmission Control Protocol (TCP)
- TCP/IP, 34–42, 48
 - application layer, 36
 - applications of, 41
 - File Transfer Protocol (FTP), 41, 48
 - host-to-host layer, 35–36
 - Internet-based applications, 48
 - internet layer, 35
 - Internet Protocol (IP), 35, 39–40
 - IP datagram, 38
 - layers, 34–36
 - network access layer, 35
 - operation of, 36–38
 - physical layer, 35
 - ports, 37
 - protocol architecture, 34–42
 - protocol interfaces, 41–42
 - segments, 37–38
 - Simple Mail Transfer Protocol (SMTP), 41, 48
 - subnetworks, 36
 - TELNET, 41, 48
 - Transmission Control Protocol (TCP), 36
 - transport layer, 35–36
 - User Datagram Protocol (UDP) and, 38–39, 41
- TDM, *see* Time division multiplexing (TDM)
- TELNET, 41, 48
- 10-Gbps Ethernet, 497–500
- Terminal equipment (TE), 338
- Terrestrial microwave, 119–120
- Text, media type, 49–50
- Text type, MIME, 753
- TFTP, *see* Trivial File Transfer Protocol (TFTP)
- Thermal noise, 89
- Third generation (3G) cellular systems, 432–440
 - bandwidth, 439
 - chip rate, 439
 - design considerations, 438–440
 - interfaces, 437–438
 - multirate, 439–440
 - personal communication networks (PCNs), 437
 - personal communication services (PCSs), 437
- Three-way handshake procedure, 671–673
- Throughput, 51, 527, 628
 - inelastic traffic, 51, 628
 - wireless LANs, 527
- Time division multiplexing (TDM), 240, 241, 248–258, 258–265
 - digital carrier systems, 253–255
 - link control, 250–253
 - statistical, 240, 241, 258–265
 - synchronous, 240, 248–258
 - use of, 240, 241
- Time division switching, 307
- Time domain, 67–70
- Time exceeded message, ICMP, 583
- Time to live, IP protocol, 577, 579
- Timers, 667, 669, 670, 674, 686
 - keepalive, 674
 - persist, 669
 - retransmission (RTO), 667, 686
 - retransmit-SYN, 670
 - transport protocol, 667
- Timestamp, 577, 585, 825
 - ICMP, 585
 - IP protocol, 577
 - reply message, 585
 - RTP, 825
- Timing, 34, 61, 355, 356, 399–400, 539–540
 - cell insertion time, 399
 - connection duration, 399
 - decision time, routing, 355
 - information update, routing, 356
 - interframe space (IFS), 802.11 MAC, 539–540

- Timing (*cont.*)
 - long term, 399
 - round-trip propagation time, 399
- TCP/IP, 34
- TFTP, 61
- traffic and congestion control, 399–400
- Top-down approach, 3–5
- Topologies, 201–202, 451–456, 454, 504
 - bus, 451–453, 454
 - defined, 451
 - digital data communication, 201–202
 - Fibre Channel, 504
 - hub, 454
 - LANs, 451–456
 - ring, 453, 455
 - star, 454
 - transmission media, choice of, 455–456
 - tree, 451–453
- Total Length field, IP protocol, 578
- Total Path Attributes Length field, BGP, 620
- Traffic, 12, 51–52, 334, 405–406, 420, 429, 433, 625–628, 631–632, 642–643, 704, 713, 808–811
 - analysis, network attack, 704
 - channels, 420, 429, 433
 - classifier, DS, 642–643
 - conditioning functions, DS PHB, 642, 642–643
 - defined, 12
 - digital channels, 429
 - dropper, DS, 642–643
 - elastic, 51–52, 625–628
 - inelastic, 51–52, 628
 - Internet, 625–628
 - ISA, 625–628
 - marker, DS, 642–643
 - meter, DS, 642–643
 - multimedia, 51–52
 - padding, 713
 - parameters, VCC and VCP, 334
 - real-time, 808–811
 - shaper, DS, 642–643
 - shaping, 405–406
 - specification (Tspec), ISA, 631–632
- Traffic management, 386–387, 389–392, 394–406, 406–408, 464
 - ATM, 394–406
 - ATM-GFR, 406–408
 - cell delay variation (CDV), 395–398, 402–403
 - committed burst size, 391
 - committed information rate (CIT), 390
 - congestion control, 386–387, 394–406, 406–408
 - connection admission control, 402–404
 - constant bit-rate (CBR), 402–403
 - contention approach, MAC, 464
 - discard eligibility (DE), 390
 - excess burst size, 391
 - fairness, 386–387
 - frame relays, 389–392
 - guaranteed frame rate (GFR), 406–408
 - latency/speed effects, 395
 - peak cell rate (PCR), 402–403
 - quality of service (QoS), 387
 - rate management, 389–392
 - reservation approach, 387, 464
 - resource management, 400–402
 - round robin approach, MAC, 464
 - selective cell discard, 405
 - sustainable cell rate (SCR), 402–403
 - techniques, 400–406
 - timing, 399–400
 - traffic policing, 405
 - traffic shaping, 405–406
 - usage parameter control (UPC), 404–405
 - variable-bit rate (VBR), 402–403
 - virtual paths, 400–402
- Trailer, HDLC, 223
- Transfer, TFTP, 59
- Transfer encodings, MIME, 757–760
 - base64, 758–760
 - quoted-printable, 757–758
 - rules, 758
- Translator, RTP packets, 824
- Transmission, 17, 20–21, 65–101, 102–137, 181, 182–186, 202–203, 528, 565, 635, 636. *See also* Retransmission
 - analog, 84–85
 - analog and digital data, 78–86
 - asynchronous, 181, 182–185
 - attenuation, 86–87, 88
 - bandwidth, 72–78, 79, 92–93, 104
 - channel capacity, 91–96
 - communication techniques, 21
 - concepts and terminology of, 67
 - data, 65–101
 - decibels and signal strength, 99–101
 - defined, 78
 - delay distortion, 87, 89
 - digital, 84–85
 - digital data, 85–86, 181, 182–186, 202–203
 - direct link, 67
 - efficiency, 21
 - electromagnetic spectrum and frequencies of, 105
 - fiber optic, 20
 - frequency domain, 67, 70–72
 - full-duplex, 67, 203
 - guided media, 67, 103, 104–116
 - half-duplex, 67, 202–203
 - impairments, 86–91, 104
 - information, of, 20–21
 - interference, 104
 - introduction to, 66–67
 - line-of-sight (LOS), 125–129, 129–133
 - media, 21, 102–137
 - multicast, 635, 636
 - multipoint, 67
 - noise, 89–91
 - point to point, 67, 104, 106
 - priority, 565
 - protocol services, 565
 - quality of service, 565
 - receivers, 104
 - recommended reading and Web sites, 96, 133–134
 - RSVP, 635, 636
 - security, 528, 565
 - signals, 17, 67–72, 78, 80–86, 86–91, 99–101
 - simplex, 67
 - spectrum, 72
 - synchronous, 181, 182–183, 185–186
 - system, 17
 - time domain, 67–70
 - unicast, 635, 636
 - wireless LANs, 528
- Transmission Control Protocol (TCP), 36, 656, 674–693
 - congestion control, 683–693
 - connection establishment, 680
 - connection termination, 680
 - data stream push, 675
 - data transfer, 680
 - header fields, 676–680
 - implementation policy options, 680–682
 - layer, 36
 - mechanisms, 679–680
 - retransmission timer management, 683–690
 - service parameters, 677
 - service request primitives, 675
 - service response primitives, 676
 - services, 675–676
 - urgent data signaling, 675
 - use of, 656, 674
 - window management, 690–693
- Transmission impairments, 86–91, 99, 104
 - attenuation, 86–87, 88, 99
 - delay distortion, 87, 89
 - noise, 89–91
 - transmission media and, 104
- Transmission media, 21, 102–137, 451, 455–457, 503
 - coaxial cable, 112, 456
 - Fibre Channel, 503
 - guided, 67, 103, 104–116
 - LANs, 451, 455–457
 - line-of-sight, 125–129, 129–133
 - twisted pair, 104–111, 455
 - unguided, 67
 - wireless, 20, 67, 117–125, 125–129, 129–133
- Transmission time, 211–212, 232–234, 315–316, 514–517
 - circuit and packet switching, 315–316
 - high-speed LANs, 514–517
 - stop-and-wait flow control, 211–212, 232–234
- Transmit error, NRZI encoding, 510
- Transmitter, defined, 17
- Transmitter address, IEEE 802.11 MAC, 541
- Transport layer, TCP/IP, 35–36
- Transport protocols, 556, 655–698. *See also* Network service
 - connection-oriented mechanisms, 657–674
 - recommended reading and Web sites, 695
 - reliable sequencing network service, 657–665
 - timers, 667
 - Transmission Control Protocol (TCP), 656, 674–693
 - transport service (TS), 656
 - unreliable network service, 665–674
 - use of, 556–656
 - User Datagram Protocol (UDP), 656, 693–694
- Transport service (TS), 656
- Traps, SNMP, 764
- Tree topology, 447, 451–453
- Trivial File Transfer Protocol (TFTP), 57–61
 - errors and delays, 60
 - introduction to, 57
 - packets, 57–59
 - semantics, 61
 - syntax, 61

timing, 61
 transfer, overview of, 59–60
 Trunks, public telecommunications network, 303
 Tunnel, HTTP, 788
 TV signals, *see* Frequency division multiplexing (FDM)
 Twisted pair, 104–111, 455
 LAN use of, 455
 applications of, 107
 categories of, 109–111
 description of, 104, 106–107
 shielded (STP), 109, 110–111
 subscriber loops, 107
 transmission characteristics of, 107
 unshielded (UTP), 109–111
 Two-level PSK, *see* Binary phase-shift keying (BPSK)
 Type-of-service indicators, IP protocol, 577

U

UDP, *see* User Datagram Protocol (UDP)
 Unacknowledged connectionless service, LLC, 460–461
 Unbalanced configuration, HDLQ, 222
 Unguided media, *see* Wireless transmission media
 Unicast addressing, 564, 593
 Unicast strategy, multicasting, 607
 Unicast transmission, RSVP, 635, 636
 Uniform Resource Identifier (URI), 814
 Unipolar signaling, 141
 Universal Networking Information Infrastructure (UNNI), 545
 Unnumbered frames (U-frames), 224
 Unshielded twisted pair (UTP), 109–111
 Unspecified bit rate (UBR), 345, 347
 Urgent data signaling, 675
 Urgent pointer field, TCP, 679
 Usage parameter control (UPC), 404–405
 USENET newsgroups, 6
 User agent, HTTP, 786
 User agent client (UAC), 812
 User agent server (UAS), 812
 User data transfer, frame relay, 322–323
 User Datagram Protocol (UDP), 38–39, 41, 656, 693–694, 762–763
 headers, 39, 694
 SNMP and, 762–763
 TCP and, 38–39, 41
 use of, 656, 693–694
 User module (UM), wireless LANs, 524
 User plane, 321–322, 330
 ATM, 330
 frame relay, 321–322
 User response, frame relays, 393–394
 User-network interface (UNI), 338, 397–398
 ATM, 338
 Cell delay variation (CDV), 397–398

V

Variable-bit-rate (VBR), 336, 345, 346, 402–403
 connection admission control, 402–403
 GFC mechanism, 336
 non-real-time (nrt-VBR), 345, 346
 real-time (rt-VBR), 345, 346

VCC, *see* Virtual channel connection (VCC)
 Version field, 577, 590
 Very high data rate digital subscriber line (VDSL), 268–269
 Very large-scale integration (VLSI), 7, 86
 Very small aperture terminal (VST), 122
 Video, 50, 78–79, 82–83, 803–808
 analog data, 78–79, 82–83
 anchor frame, 805
 color subsampling, 803
 compression, 803–808
 discrete cosine transformation (DCT), 803–804
 fast forward/reverse searches, 804
 frame ordering, 807–808
 Huffman coding, 804
 interpolation, 806–807
 media type, 50
 motion compensation, 805
 MPEG compression algorithm, 803–805
 prediction, 805–806
 quantization, 804
 random access, 804
 run-length encoding, 804
 scaling and color conversion, 803
 Source Input Format (SIF), 803
 transmission, 78–79, 82–83
 Video type, MIME, 756
 Videocassette recorders (VCRs), 16
 Virtual channel connection (VCC), 331–335
 call establishment, 332
 call sequence integrity, 334
 characteristics of, 334–335
 connection uses, 333–334
 defined, 331
 meta-signaling channel, 335
 quality of service (QoS), 334
 semipermanent, 334, 335
 switched, 334
 terminology for, 333
 traffic parameters, 334
 user-to-network signaling channel, 335
 Virtual Channel Identifier (VCI), ATM, 337
 Virtual circuits, 310, 321–313, 318–319
 approach, packet switching, 310, 321–313
 defined, 318
 X.25 interfacing, 317–319
 Virtual path connection (VPC), 331–333, 334–335, 400–402
 advantages of, 331
 aggregate peak demand, 401–402
 ATM resource management, 400–402
 call establishment, 332
 call sequence integrity, 334
 characteristics of, 334–335
 customer controlled, 335
 defined, 331
 identifier restriction, 334
 network controlled, 335
 quality of service (QoS), 334
 semipermanent, 334, 335
 statistical multiplexing, 402
 switched, 334
 terminology for, 333
 traffic management and congestion control, 400–402
 traffic parameters, 334

Virtual Path Identifier (VPI), ATM, 336
 Virtual private networks (VPN), 596–599
 Voiceband signals, *see* Frequency division multiplexing (FDM)
 Voice over IP (VoIP), 811

W

WAN, *see* Wide area networking (WAN)
 Wavelength, defined, 70
 Wavelength division multiplexing (WDM), 247–248
 Web access, *see* Hypertext Transfer Protocol (HTTP)
 Web sites, 5–6, 54, 96, 134, 270, 290, 324, 349, 441, 479, 506, 551, 600, 651, 695, 740, 771, 796, 832
 asynchronous transfer mode (ATM), 349
 cellular wireless networks, 441
 data communications, 5–6
 data transmission, 96
 Domain Name System (DNS), 796
 electronic mail, 770–771
 high-speed LANs, 506
 Hypertext Transfer Protocol (HTTP), 796
 Internet Protocol (IP), 600
 internetwork operation, 651
 local area network (LAN), 479
 multimedia applications, 832
 multiplexing, 270
 network security, 740
 protocol architecture, 54
 Simple Network Management Protocol (SNMP), 771
 spread spectrum, 290
 switched communications networks, 324
 transmission media, 134
 transport protocols, 695
 wireless LANs, 551
 Weighted fair queuing (WFQ), 634
 White noise, 89
 Wide area networking (WAN), 15, 22–23, 295–296, 297–327, 328–350, 351–376, 377–412, 413–443
 asynchronous transfer mode (ATM), 296, 328–350
 cellular wireless networks, 296, 413–443
 circuit switching, 295, 298, 301–304, 304–309, 315–316
 congestion control in data networks, 296, 377–412
 corporate needs, 15
 frame relay, 319–323
 packet switching, 295, 298, 309–317, 317–319, 319–323
 routing, 296, 351–376
 switched communications networks, 296, 297–327, 351–376
 use of, 22–23, 295–296
 X.25 interfacing standard, 317–319
 Wi-Fi Protected Access (WPA), 550, 737–739
 access control, 738–739
 authentication, 737–738
 LAN standards, 550
 network security, 737–739
 privacy with message integrity, 738, 739

- Window field, TCP, 679
 - Window management, 690–693
 - dynamic window sizing, 691
 - fast recovery, 693
 - fast retransmit, 691–693
 - slow start, 690–691
 - TCP congestion control, 683–690
 - Wireless Fidelity (Wi-Fi), 532, 550, 737–739
 - Alliance, 532, 737
 - network security, 737–739
 - Protected Access (WPA), 550, 737–739
 - WLANs, 550
 - Wireless LANs (WLAN), 445, 483, 522–553
 - access point (AP), 532
 - ad hoc networking, 526
 - applications, 524–526
 - architecture, 531–533
 - association-related services, 535
 - basic services set (BSS), 532
 - control module (SM), 524
 - cross-building interconnect, 525
 - distribution system (DS), 532, 534–535
 - extended service set (ESS), 533
 - high-speed, 483
 - IEEE 802.11, 523, 531–535, 535–543, 543–549, 549–550
 - independent basic services set (IBSS), 532
 - infrared (IR), 528–530
 - introduction to, 445, 523
 - LAN extension, 524–525
 - medium access control (MAC), 534–535, 535–543
 - nomadic access, 525–526
 - overview of, 523–528
 - physical layer, 457, 496–497, 543–549
 - portal, 532
 - recommended reading and Web sites, 550–551
 - requirements, 526–528
 - security considerations, 549–550
 - services, 533–535
 - spread spectrum, 528, 530
 - technology, 528–530
 - user module (UM), 524
 - Wi-Fi Protected Access (WPA), 550
 - Wireless Fidelity (Wi-Fi) Alliance, 532
 - Wireless transmission, 20, 67, 117–125, 125–129, 129–133. *See also* Cellular wireless networks; Wireless LANs
 - antennas, 117–119
 - atmospheric absorption, 132
 - broadcast radio, 124
 - defined, 20
 - free space loss, 129–132
 - frequency bands, 126
 - ground waves, 125
 - infrared, 125
 - line-of-sight, 125–129, 129–133
 - microwave frequencies, 117
 - microwave systems, 119–124
 - multipath interference, 132–133
 - propagation, 125–129
 - radio range, 117
 - refraction, 128, 133
 - sound waves, 125
 - unguided media, 67, 103
 - wireless media, 20, 67, 117–125, 125–129, 129–133
 - World Wide Web (WWW), *see* Hypertext Transfer Protocol (HTTP)
 - WPA, *see* Wi-Fi Protected Access (WPA)
 - Write request (WRQ) packet, 58
- X**
- X.25 interfacing standard, 317–319
 - Link Access Protocol-Balanced (LAPB), 318–319
 - virtual circuits, 318–319
 - xDSL, 268–269
- Z**
- Zone, *see* DNS, 779–781