



## A systematic review on hybrid EEG/fNIRS in brain-computer interface

Ziming Liu<sup>a</sup>, Jeremy Shore<sup>a</sup>, Miao Wang<sup>c</sup>, Fengpei Yuan<sup>a</sup>, Aaron Buss<sup>b</sup>, Xiaopeng Zhao<sup>a,\*</sup>

<sup>a</sup> Department of Mechanical, Aerospace, and Biomedical Engineering, University of Tennessee, Knoxville, TN, 37996, USA

<sup>b</sup> Department of Psychology, University of Tennessee, Knoxville, TN, 37996, USA

<sup>c</sup> Department of Electrical and Computer Engineering, Miami University, Oxford, OH, USA

### ARTICLE INFO

#### Keywords:

Brain-computer interface  
Hybrid neuroimaging  
EEG/fNIRS  
Systematic review

### ABSTRACT

As a relatively new field of neurology and computer science, brain computer interface (BCI) has many established and burgeoning applications across scientific disciplines. Many neural monitoring technologies have been developed for BCI studies. Combining multiple monitoring technologies provides a new approach that synthesizes the advantages and overcomes the limitations of each technology. This article presents a systematic review on the applications, limitations, and future directions for the hybridization of electroencephalography (EEG) and functional near-infrared spectroscopy (fNIRS) into one synchronous multimodality. This review investigated research questions on design and usability of hybrid EEG-fNIRS studies. In this article, 765 papers were included in the initial search and 128 papers were selected through the PRISMA protocol. The review results show the possibility of improving the performance of hybrid EEG-fNIRS by optimizing the feature extraction algorithms and physical designing as well as expanding more possible applications in information processing related fields.

### 1. Introduction

Brain computer interface (BCI) translates brain activity associated with a subject's intention into commands to communicate with or control an external device, bypassing the physiological motor output system. With the development of BCI, many prospective applications have been proposed for mental health and disabilities for individuals. BCI research has been considered as an effective approach to assist people with physical disabilities and mental diseases.

To maximize the application effect of BCIs, an optimized signal collector is required to obtain real-time information from brain activity in a convenient and effective method, with less set-up time and long-term stability. Currently, popular BCI monitoring technologies include Electroencephalography (EEG) [1], functional Magnetic Resonance Imaging (fMRI) [2], Magnetoencephalography (MEG) [3] and functional Near-Infrared Spectroscopy (fNIRS) [4], which each have their own advantages and limitations. Combining multiple monitoring technologies provides a new approach that synthesizes the advantages of each technology as well as overcomes the limitations. Hybrid EEG-fNIRS is one of the feasible methods of improving BCIs' performance. It simultaneously measures from both electrical and hemodynamic activity on the cerebral cortex, which may provide more detailed brainwave information in nearly real time by combining their features. This

multimodality provides a novel processing approach to expand existing BCI applications.

EEG records electrical activities in the brain from electrodes placed on the scalp [5]. Because of its high temporal resolution, convenient wearability and low cost, EEG has been considered as the most actively used research tool in BCI. However, the low spatial resolution limits the EEG to record functionalities of brain which cannot accurately locate associated cortical sources [6]. To further enhance the performance of BCIs, hybrid EEG/fNIRS was proposed. In contrast to EEG, fNIRS uses near-infrared-range light to measure the concentration change of oxy- and deoxy-generated hemoglobin (HbO and HbR) and is not susceptible to electrical noise. The main limitation of fNIRS is the long response lag because the hemodynamic response requires time to reach its maximum amplitude, which means that the measurement cannot be used in real-time applications [7]. Although hybrid EEG-fNIRS is considered to combine the advantages of EEG and fNIRS in a way that compensates for the limitations of each modality, the possibilities of using hybrid EEG-fNIRS to discriminate specific cerebral activity features are not investigated comprehensively. There are two problems of addressing the current state of arts in hybrid EEG-fNIRS applications in BCIs.

One main challenge is determining an organized structure to categorize hybrid EEG-fNIRS systems in BCIs. Since the role of fNIRS in each BCI system can vary, such as complements to achieve the same goal as

\* Corresponding author.

E-mail address: [xzhao9@utk.edu](mailto:xzhao9@utk.edu) (X. Zhao).

<https://doi.org/10.1016/j.bspc.2021.102595>

Received 5 November 2020; Received in revised form 4 March 2021; Accepted 26 March 2021

Available online 2 April 2021

1746-8094/© 2021 Elsevier Ltd. All rights reserved.

EEG or to perform independent duties in the same experiment. Because of the various proposals for the EEG-fNIRS combination, there are no simple categories that can explain the roles and operations in different lines of research. Another issue is the complexity of determining the usability of hybrid EEG-fNIRS applications in BCIs. As a developing methodology in BCI related research, the efficacy of additional communication channels and external features can be influenced by channel locations, user abilities and other different variables. Therefore, it is difficult to determine the efficiency of different hybrid EEG-fNIRS structures across these various applications. To comprehensively examine the efficiency of hybrid EEG-fNIRS, various data analysis algorithms have been developed to analyze patterns from EEG/fNIRS data [8]. Machine learning algorithms, which are widely used in brain signal analysis, have been developed as effective tools for compensating the high variability in EEG analysis [9]. However, the usability of machine learning algorithms in EEG-fNIRS analysis is still in an early stage.

This paper mainly discusses the hybrid EEG-fNIRS from usability, integration of structure and algorithms perspectives to evaluate and represent the state of the art and its limitations.

## 2. Methodology

A systematic review was conducted following the Preferred Reporting Items for Systematic Reviews and Meta-Analyses (PRISMA) protocol [10] and the Problem, Intervention, Comparison, and Outcomes (PICO) statement [11]. The flow diagram of PRISMA with results in each categorization section is shown in Fig. 1. As shown, the protocol for research here included three main iterative steps: (1) Initial Search: investigated related studies based on the keyword combinations in selected databases. (2) Prescreening: selected articles based on their titles and abstracts using the designed criteria. (3) Qualifying: read through the full text of the selected articles to make sure they are qualified.

### 2.1. Search strategy

The acquisition of relevant papers that used or studied an EEG-fNIRS hybridization was conducted on PubMed, Scopus and Web of Science as the literature collection source base. The selected articles were covered from the first published study utilizing hybrid EEG-fNIRS application in BCI to the most recent. Only full text articles written by English were included. Other publication forms, such as proceeding papers, unpublished working papers, dissertations, newspapers and books etc. are

excluded. The keyword combinations of related studies focusing on analyzing the usability of different applications and the integration of EEG-fNIRS' structures and algorithms used in this paper is shown as Table 1. Using a combination of all the keywords resulted in 765 articles in the initial search.

### 2.2. Prescreening and qualifying criteria


The prescreening criteria are based on the titles and abstracts in the database. First, duplicated articles under different titles are removed. Then, articles were excluded if they 1) had no hybridization of EEG and fNIRS in physical set up or feature analysis; and 2) had no information about the analysis of populations, interventions, comparisons, outcomes, and study design. After prescreening and excluding duplicates, 147 papers remained.

The articles were then subjectively screened by authors to qualify the conformity and correspondence with the remaining studies. In the qualifying process, 6 studies that researched or incorporated EEG and NIRS were excluded because the near-infrared spectroscopy data were used for applications other than BCI. 12 studies compared the performances of EEG, fNIRS, and EEG-fNIRS together to determine if EEG-fNIRS was worth hybridizing. Such hybrid systems will be dubbed as "EEG-fNIRS" in this review. 5 studies compared the performances of EEG, fNIRS, EEG-fNIRS, and a fourth modality to measure differences in performance between EEG-fNIRS and other configurations, such as transcranial alternating current stimulation (tACS). The information from these studies was only confined to the EEG and fNIRS portion.

**Table 1**  
Keyword Combinations for EEG-fNIRS Study Selection.

1	"BCI" AND "fNIRS" AND "EEG"
2	"BMI" AND "fNIRS" AND "EEG"
3	"Hybrid" AND "fNIRS" AND "EEG"
4	"Combined" AND "fNIRS" AND "EEG"
5	"Modalities" AND "EEG" AND "fNIRS"
6	"Strategy" AND "EEG" AND "fNIRS"
7	("ML" OR "DL") AND "EEG" AND "fNIRS"

(Abbreviation used as BCI = "Brain Computer Interface", BMI = "Brain Machine Interface", ML = "Machine Learning", DL = "Deep Learning", fNIRS = "functional Near-Infrared Spectroscopy", and EEG = "Electroencephalography". Search was done using both the abbreviations and the full names of the key words.)



**Fig. 1.** PRISMA flow diagram for the initial study selection. (Abbreviation used as ML = "Machine Learning", DL = "Deep Learning", fNIRS = "functional Near-Infrared Spectroscopy", and EEG = "Electroencephalography").

### 3. Results

After qualifying screening, 128 studies for this review were extracted from the initial 765 candidates. The 128 remaining studies were utilized to investigate the features of the hybridization of EEG-fNIRS in usability, integration of structures and algorithms, their limitations and future research directions.

As shown in Table 2, six categories of hybrid EEG-fNIRS tasks were selected based on the remaining papers. Mental tasks include studies that classify several mental states, such as workload, fatigue, and alertness, which can be reliably distinguished by recognizing patterns in EEG and fNIRS features. Emotion measurement tasks are studies that identify specific emotional states, such as sympathy, valence/arousal, and social rankings from EEG and fNIRS features. Motor control tasks include experiments which utilize the higher performance of hybrid EEG-fNIRS to further distinguish BCI-based motor control, such as sensorimotor rhythms. Perception tasks consist of studies aimed at distinguishing various biomarkers of perception including visual-spatial attention, auditory attention and olfactory attention. Cognitive evaluation and rehabilitation tasks include studies that use hybrid EEG-fNIRS systems for evaluation and rehabilitation training purposes in the context of mental diseases or disabilities. Cognitive improvement tasks refer to studies aimed at improving general human cognitive abilities.

To evaluate and determine the system integration, usability and analysis algorithms of hybrid EEG-fNIRS in BCI applications, remaining studies were categorized based on the general characteristics regarding: stimulus modalities, task types, measured cortical regions (EEG and fNIRS), and role of operations to differentiate the integrated functions of hybrid EEG-fNIRS as simultaneous or sequential. The resulting features of the hybrid EEG-fNIRS studies are shown in detail in Table 3. The stimulus modalities and task types categories demonstrate the range of tasks utilized in hybrid EEG-fNIRS studies. Monitored cortical regions of EEG and fNIRS and role of operations categories are used to analyze the integration of designing EEG-fNIRS hybridization strategies in different BCI applications. The information in each categorization is presented in Tables 4 and 5 correspondingly. The modalities associated with BCI applications in the remaining hybrid EEG-fNIRS related studies are represented in Table 4. To evaluate the integration of hybrid EEG-fNIRS, Table 5 shows the regions of cortex that EEG and fNIRS detected and whether they cooperated for the same goal or had decentralized duties.

Table 6 shows the state of art of machine learning algorithms in EEG-fNIRS and their performance in terms of classification. The classification algorithms include various machine learning methods and their ensemble learning methods. The result of Table 6 demonstrates the methodology of normalized feature generalization and their corresponding performance according to different neural network architectures. As a comparison, the accuracies of different studies are presented to evaluate their performances. The advantages of each algorithm depend on their dominances in the purpose of architecture design.

### 4. Discussion

#### 4.1. Combined EEG-fNIRS applications

As shown in Table 3, mental task is the most studied topic,

**Table 2**  
Proportions of using hybrid EEG-fNIRS in different BCI tasks.

Task Categories	References	Count	Percentage
Mental tasks	[12–32]	21	32.8%
Emotion measurement task	[33–38]	6	9.4%
Motor Control Task	[39–53]	15	23.4%
Perception Task	[54–62]	9	14.1%
Clinical Evaluation & Rehabilitation Task	[63–70]	8	12.5%
Cognitive improvement Task	[71–75]	5	7.8%

**Table 3**  
Categorization Details of Relative Hybrid EEG-fNIRS Studies.

<b>Stimulus modalities:</b>	Visual, auditory, operant, workload, olfactory and external stimulus
<b>Task types:</b>	Active and passive tasks
<b>Detected cortex regions (EEG):</b>	Prefrontal, motor, temporal, occipital, visual/auditory, whole head
<b>Detected cortex regions (fNIRS):</b>	Prefrontal, motor, temporal, occipital, visual/auditory, whole head
<b>Role of operations:</b>	Simultaneous and sequential

**Table 4**  
Applications of each modalities in hybrid EEG-fNIRS.

Applications	Stimulus Modalities	Mental Tasks	Reference	
Mental workload	Workload	Passive	[12–14,17,19,20–22,25,30,32,60]	
	Visual	Passive	[26,31]	
Math ability	Workload	Passive	[15,18]	
ALS	Visual	Passive	[65,68]	
ADRD	Verbal	Passive	[63]	
ADHD	Operant	Active	[66]	
	Verbal	Active	[67]	
Novel clinical applications	Visual		[61,76]	
	Verbal	Passive	[23]	
	N/A		[40,69]	
Emotion perception	Verbal		[33]	
	Visual	Passive	[34–38]	
Epilepsy	Operant	Passive	[64,70,77–83]	
		N/A	[81]	
Facial recognition	Visual	Passive	[55,84]	
Language reorganization	Verbal	Passive	[85,86]	
		Active	[39,41,43,44,46,50–53]	
Motor control	Operant	Passive	[35,42,47,49]	
		Passive	[87–89]	
		Passive	[90,91]	
Measurement system design	Workload	Active	[45]	
	Operant	Passive	[44,92]	
Sedation	Workload	N/A	[93]	
		Passive	[24]	
Signal classification	Operant	Active	[94–97]	
		Passive	[72,98–101]	
		Passive	[75,102,103]	
Transcranial stimulation	External	Visual	[59,104]	
		Verbal	Active	[105]
		Active	[71,106]	
Visual Stimulation	Visual	Passive	[73]	
		Active	[72]	
Visual Processing	Visual	Passive	[58,107]	
		Passive	[57,74]	
Visual and Auditory Stimulus	Visual & Auditory	Passive	[54,108]	
Olfactory Stimulus	Olfactory	Active	[56]	

Abbreviation used as “ALS = “Amyotrophic Lateral Sclerosis”, “ADRD” = “Alzheimer and related dementia”.

comprising 32.8% of selected studies. As a relatively new BCI technology, EEG-fNIRS has become a popular approach since it provides higher accuracy in decoding brain activities with less electrical noise in specific cortex regions. However, the mental status, such as fatigue [128] and alertness [129], has been considered as a synchronization of multiple regions. Analyzing one or few cortex regions with higher accuracy may not be able to provide more information. Several studies [12,13,21,56,76] showed that mental tasks using EEG-fNIRS signals achieve comparable classification performance with those using EEG signals, indicating the need for advanced algorithms on EEG-fNIRS signal analysis and fusion. According to the result from contained studies related to mental tasks, proposed applications of using mental status change as the indicator are involved in driving status monitoring [17,20,29] and user engagement measurement [28].

**Table 5**  
Applications of electrode/optodes selection in hybrid EEG-fNIRS experiments.

Applications	Electrodes regions	Optodes regions	Roles of operations	Studies
Mental workload	Occipital cortex	Occipital cortex	Simultaneous	[25]
	Prefrontal cortex	Whole head	Not Specified	[12]
	Prefrontal cortex	Prefrontal cortex	Not Specified	[13,60]
	Prefrontal cortex	Prefrontal cortex	Simultaneous	[14,21,22]
	Central cortex	Central cortex	Sequential	[49]
	Whole head	Central cortex	Simultaneous	[50]
Math ability	Occipital cortex	Prefrontal cortex	Simultaneous	[26]
	Prefrontal cortex	Not Specified	Simultaneous	[15]
ALS	Whole head	Prefrontal cortex	Simultaneous	[65,68]
ADRD	Frontal cortex	Whole head	Simultaneous	[99]
ADHD	Prefrontal cortex	Prefrontal cortex	Simultaneous	[66]
	Whole head	Prefrontal cortex	Simultaneous	[67]
	Prefrontal cortex	Whole head	Simultaneous	[76]
Novel clinical applications	Whole head	Whole head	Simultaneous	[23,40,61]
	Motor cortex	Motor cortex	Simultaneous	[69]
Emotion perception	Prefrontal cortex	Prefrontal cortex	Simultaneous	[34]
	Left hemisphere	Whole head	Simultaneous	[36]
	Prefrontal cortex	Whole head	Simultaneous	[37]
	Central cortex	Central cortex	Simultaneous	[38]
Epilepsy	Temporal cortex	Temporal cortex	Simultaneous	[64]
	Central cortex	Central cortex	Simultaneous	[70,77]
	Frontal cortex	Frontal cortex	Simultaneous	[79]
Facial recognition	Temporal cortex	Temporal cortex	Not Specified	[55,84]
	Whole head	Prefrontal cortex	Simultaneous	[69]
Language reorganization	Whole head	Temporal cortex	Simultaneous	[86]
	Whole head	Motor cortex	Simultaneous	[41]
	Motor cortex	Whole head	Simultaneous	[42]
	Central cortex	Whole head	Sequential	[46]
Motor control	Prefrontal cortex	Prefrontal cortex	Sequential	[43]
	Whole head	Whole head	Simultaneous	[44]
	Motor cortex	Motor cortex	Simultaneous	[39]
	Whole head	Central cortex	Simultaneous	[51,53,109]
	Central cortex	Prefrontal cortex	Simultaneous	[52]
	Motor cortex	Motor cortex	Simultaneous	[87]
Measurement system design	Whole head	Whole head	Simultaneous	[90,91,93]
	Temporal cortex	Temporal cortex	Simultaneous	[92]
	Whole head	Left hemisphere	Not Specified	[45]
Sedation	Whole head	Prefrontal cortex	Simultaneous	[89]
	Frontal cortex	Frontal cortex	Simultaneous	[24]
	Whole head	Whole head	Simultaneous	[94,96]

**Table 5 (continued)**

Applications	Electrodes regions	Optodes regions	Roles of operations	Studies
Signal classification	Motor cortex	Motor cortex	Simultaneous	[99]
	Prefrontal cortex	Prefrontal cortex	Simultaneous	[101,103,104]
	Occipital cortex	No details	Simultaneous	[59]
Transcranial stimulation	Whole head	Central cortex	Simultaneous	[105]
	Motor cortex	Motor cortex	Not Specified	[71]
Visual Stimulation	Prefrontal cortex	Prefrontal cortex	Simultaneous	[106]
	Whole head	Whole head	Simultaneous	[72]
Visual Processing	Occipital cortex	Occipital cortex	Simultaneous	[58,107]
	Occipital cortex	Occipital cortex	Simultaneous	[57,74]
Visual/Auditory Stimulus	Occipital cortex	Occipital cortex	Simultaneous	[54]
	Whole head	Whole head	Simultaneous	[108]

Abbreviation used as “ALS = “Amyotrophic Lateral Sclerosis”, “ADRD” = “Alzheimer disease and related dementia”.

Motion control also contains high proportion of selected studies with 23.4%. Motion control studies can be categorized into active tasks [42–44,47,50,51] and passive tasks [41,45,46,48–50]. In these tasks, hand motion is a dominated experiment setting in classifying motor imagery commands and differentiating actual hand movements. Compared with mental and motor control tasks, there are fewer applications of hybrid EEG-fNIRS in other tasks, especially for clinical tasks. This limitation is probably due to insufficient classification approaches in emphasizing the advantages of fNIRS in the analysis of diseases or disabilities.

Emotion measurement tasks and motor control tasks utilizing hybrid EEG-fNIRS provided significant improvement in extracting features from brain activities [28,42,45,60,130,131]. Because of the limitation of experiment settings, compared with other tasks, emotion measurement and motor control tasks require relatively longer period in each trial to measure corresponding cortical activations. The relative longer time in measurement may weaken the influence from fNIRS signal’s delay. Previous studies of motor control tasks found that the delay of fNIRS may cause the growth of moving artifact of remote-control devices. Future BCI-devices may consider to use supplemental signals such as Electromyography (EMG) to help to reduce artifacts in EEG-fNIRS measurements [41].

Unlike other tasks, measurements during perception tasks were limited by the structure of related cortex. Occipital cortex is mainly considered as the corresponding regions of visual, spatial, and relative attentions which is often decoded in perception classifications. A few studies on visual perception showed that adding fNIRS signals measured from the same region as EEG does not lead to significant improvement on the performance of BCI signal analysis [54,55,59,64]. It is hypothesized that EEG signal is good enough to distinguish brain evoked states on associated region of interest, such as occipital cortex [132]. Experiment designs compatible for hybrid EEG-fNIRS are required for further study in perception analysis, especially on maximizing fNIRS function in the analysis.

In Table 4, it is important to observe that most of the studies were designed as passive mental tasks. The reason is assumed that, in the state-of-art of hybrid EEG-fNIRS measure, the primary goal is classifying relative cognitive states with combined EEG-fNIRS features. According to stimulus modalities listed in the table, visual, operant and workload stimulus dominate the proportions. Moreover, except in specific applications (math abilities, mental workload), which have explicit research purposes on defining mental responses in different mental states, most studies still use traditional tasks such as n-back or motor imagery to



**Table 6**  
The state of art of machine learning algorithms in EEG-fNIRS.

Classification	Neural Network Architecture	Features	Performance	References
Classic Machine Learning	SVM	1) much simpler to train 2) easier to find a robust model.	Focus on relatively small data sets	[110–115]
	LDA			[94, 116–120]
DNN	DNN	Training these deep architectures is complicated, as the process gets slower the more layers are	EEG: accuracy of about 80% [121] fNIRS: accuracy of 94% [121]	[116,121]
RNN (temporal)	LSTM RNN	Input data are transformed into a 3-D tensor with standard dimensions of an LSTM-RNN.	Accuracy to 98.2% [122]	[123,124] [122]
CNN (spatial)	Convolutional Neural Networks (CNNs)	Implementation of neural networks where neurons are connected to portions of signals and or images that are close in time and/or space using trains of spikes (binary temporal events) transmitted among spatially located synapses and neurons [126]	An accuracy ranging between 96.9% and 100% [125]	[125]
SNN	SNN	To verify the efficacy of LDA classifier, RLDA classifier was used as a weak learner [127]	Outperformance SVM by 11% [126]	[126]
Ensemble learning	SVM + LDA		significant increases in the bitrate and accuracy [127]	[127]

evaluate the performance of the hybridization of EEG-fNIRS in exploiting more functions. It may provide a new approach in regulating the efficient measurement in determining the EEG-fNIRS performance by developing more suitable stimulus using EEG-fNIRS according to its high spatial resolution on cortical regions.

According to the result from Table 5, most of the studies used simultaneous EEG-fNIRS to demonstrate feasibility in further research. After counting the number of detected cortex regions for both EEG and fNIRS, the distribution of different regions in both EEG and fNIRS are approximately even when used in the same application. From the observation, it is hypothesized that the node arrangement of combining EEG and fNIRS is still unclarified and the arrangement may be one of the constraints of improving its performance. Thus, one avenue for future research is comparing hybrid EEG-fNIRS performance with various arrangements. It is also interesting to see the arrangement of optodes and electrodes are disparate between the attention on optimizing system processing and measuring specific brain activations. On the purpose of developing system processing, optodes and electrodes are mainly located in the same regions. To emphasize the weights of experimental related cortex regions in measuring, electrodes are primarily used to measure event-related desynchronizations (ERD) from brain oscillatory as well as optodes which set on the implicated cortex regions to accentuate the signal on these regions.

#### 4.2. Machine learning algorithms in EEG-fNIRS

Multimodal EEG-fNIRS data can provide superior performance metrics, and different classification procedures have been applied to combined EEG-fNIRS BCI [94,110–112,114–121,123–126,133–143]. Specifically, by employing support vector machine (SVM) [110–115] or linear discriminant analysis (LDA) [94,116–120] (which are as the classic machine learning methods), the BCI signals have been classified by EEG power spectral densities and fNIRS signal amplitudes. Furthermore, linear discriminant analysis ensemble classifiers have been employed in [127], to increase the bitrate as well as the classification accuracy for fNIRS-BCI datasets. The advantages of the classic learning methods are that they are simple to train and easy to find a good robust model. However, the computational cost would grow linearly with the size of the data set, which implies that the aforementioned methods are suitable for relatively small data sets with fewer outliers.

For the complex non-linear transformations-classifications, Deep Neural Networks (DNN) have been applied [116,121]. By employing few EEG recording channels via DNN, an average accuracy of about 80% can be achieved [121]; while regarding fNIRS, classified mental tasks through DNN can achieve an accuracy of 94% [121]. Moreover, DNN can neither provide memory capabilities or sequential information control nor encode the spatio-temporal information [138], multiple technological developments have been allowed for deep learning

evolution, e.g., either developing the neural networks where outputs are fed back into the network in a sequential manner by recurrent neural networks (RNNs) with sensitivity and specificity of 89.7% and 95.5% respectively [122–124], or encoding temporal and/or spatial information standard by convolutional neural networks (CNN) to achieve an accuracy ranging between 96.9% and 100% [125]. In addition, considering the brain functions as a spatio-temporal information processing machine, Spiking Neural Network (SNN) has been introduced to construct and train in an unsupervised mode with a recurrent 3D SNN reservoir, to learn the spike sequences. In [126], the performance of SNN can outperformance SVM by 11%.

#### 4.3. Prospects for future research

Based on the 128 selected articles, the correlation between EEG and fNIRS signals are not fully understood and the challenge of combining the advantages of electrical and optical measurements still maintains. To promote the innovation of EEG/fNIRS applications on the purpose of maximizing the advantages of combination, more future research is needed to explore possible applications, integrations, and algorithms in EEG/fNIRS analysis. The majority of selected studies appropriates EEG-fNIRS by combining collected electrical and optical handcrafted features for classification purpose. In some recent studies, machine learning algorithms play significant roles in integrating features extracted from EEG and fNIRS into multidimensional feature vectors, but the advantages of spatial information on local regions from fNIRS and temporal information on whole head from EEG were not emphasized. Furthermore, as a starting stage technology, combined EEG/fNIRS does not have uniform, standardized procedure due to many different methods regarding signal processing and analysis which makes the comparability and interpretation difficult. Therefore, effective research methods for comparison and interpretation can be further pursued in the next step. Splitting measured cortical functions may provide unique approaches to emphasize the spatial performance from fNIRS as well as temporal performance from EEG which is also convenient in comparison and interpretation.

The advantages of EEG's temporal resolution can be utilized by measuring oscillatory correlates (ERP or ERD/ERS) from whole head to detect brain evoked potentials. Because of fNIRS high spatial resolution, optodes can be set on the local region, such as occipital or prefrontal regions to measure significant attentional or visual processes. Previous studies have demonstrated the correlation between cortical connectivity and sensory processing in different mental states [144,145]. In this case, using combined EEG-fNIRS may provide a possibility in the study of measuring complex information processing between different cortex, such as driving, language or mental disease evaluation processes. Compared with fMRI which is the main device has been used in measuring cortical connectivity, combined EEG-fNIRS may be able to

implement a portable experimental environment for expanding more studies.

## 5. Conclusion

This article presents a systematic review of studies evaluating the usability and designing of hybrid EEG-fNIRS in different applications of BCIs. The overall results demonstrates that the application of combined EEG-fNIRS is still in an early stage and suggest that it may be potentially beneficial in improving the algorithms and physical system designing of hybrid EEG-fNIRS in the near future, such as emphasizing spatial and temporal advantages from fNIRS and EEG accordingly by designing advanced feature extraction methodologies and splitting nodes in different targeted cortical functions. Moreover, it is necessary to continue developing more possible applications with hybrid EEG-fNIRS, especially for complex information processing related fields.

Since the research in EEG-fNIRS is relatively new, the number of studies included in this review is relatively small. Studies were selected from the first published study utilizing hybrid EEG-fNIRS recording in BCI related applications to the most recent to maximize the quantity of studies to analyze. However, some of these studies may not be able to represent the state of art in the hybridization of EEG and fNIRS. These studies were cited as references, but not the direct evidence in observations.

## Declaration of Competing Interest

The authors declare that they have no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

## References

- [1] R. Foong, et al., Assessment of the efficacy of EEG-based MI-BCI with visual feedback and EEG correlates of mental fatigue for upper-limb stroke rehabilitation, *IEEE Trans. Biomed. Eng.* 67 (3) (2019) 786–795.
- [2] G. Valente, et al., Optimizing fMRI experimental design for MVPA-based BCI control: combining the strengths of block and event-related designs, *NeuroImage* 186 (2019) 369–381.
- [3] S. Roy, et al., Channel selection improves meg-based brain-computer interface, in: 2019 9th International IEEE/EMBS Conference on Neural Engineering (NER), IEEE, 2019.
- [4] C. Li, et al., A between-subject fNIRS-BCI study on detecting self-regulated intention during walking, *IEEE Trans. Neural Syst. Rehabil. Eng.* 28 (2) (2020) 531–540.
- [5] J. Kang, et al., Transcranial recording of electrophysiological neural activity in the rodent brain in vivo using functional photoacoustic imaging of near-infrared voltage-sensitive dye, *Front. Neurosci.* 13 (2019) 579.
- [6] R. Abiri, et al., Decoding attentional state to faces and scenes using EEG brainwaves, *Complexity* 2019 (2019) 1–10.
- [7] V. Quresima, M. Ferrari, A Mini-review on Functional Near-infrared Spectroscopy (fNIRS): Where Do We Stand, and Where Should We Go? In *Photonics, Multidisciplinary Digital Publishing Institute*, 2019.
- [8] N. Sengupta, et al., Integrating space, time, and orientation in spiking neural networks: a case study on multimodal brain data modeling, *IEEE Trans. Neural Netw. Learn. Syst.* 29 (11) (2018) 5249–5263.
- [9] K.-R. Müller, et al., Machine learning for real-time single-trial EEG-analysis: from brain-computer interfacing to mental state monitoring, *J. Neurosci. Methods* 167 (1) (2008) 82–90.
- [10] D. Moher, et al., Preferred reporting items for systematic reviews and meta-analyses: the PRISMA statement, *BMJ* 339 (2009) b2535.
- [11] W.S. Richardson, et al., The well-built clinical question: a key to evidence-based decisions, *ACP J. Club* 123 (3) (1995) A12–3.
- [12] H. Aghajani, M. Garbey, A. Omurtag, Measuring mental workload with EEG+fNIRS, *Front. Hum. Neurosci.* 11 (2017) 359.
- [13] F. Al-Shargie, et al., Mental stress assessment using simultaneous measurement of EEG and fNIRS, *Biomed. Opt. Express* 7 (10) (2016) 3882.
- [14] F. Al-Shargie, T.B. Tang, M. Kiguchi, Assessment of mental stress effects on prefrontal cortical activities using canonical correlation analysis: an fNIRS-EEG study, *Biomed. Opt. Express* 8 (5) (2017) 2583.
- [15] C. Artemenko, et al., Individual differences in math ability determine neurocognitive processing of arithmetic complexity: a combined fNIRS-EEG study, *Front. Hum. Neurosci.* 13 (2019) 227.
- [16] Y. Chen, et al., Relationship between amplitude of resting-state fNIRS global signal and EEG vigilance measures, in: 2017 39th Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE, 2017.
- [17] C.-H. Chuang, et al., Brain electrodynamic and hemodynamic signatures against fatigue during driving, *Front. Neurosci.* 12 (2018) 181.
- [18] S. Firooz, S.K. Setarehdan, IQ estimation by means of EEG-fNIRS recordings during a logical-mathematical intelligence test, *Comput. Biol. Med.* 110 (2019) 218–226.
- [19] L.M. Hirshfield, et al., Combining electroencephalograph and functional near infrared spectroscopy to explore users' mental workload, in *Foundations of augmented cognition*, in: D.D. Schmorrow, I.V. Estabrooke, M. Grootjen (Eds.), *Neuroergonomics and Operational Neuroscience*, Springer Berlin Heidelberg, Berlin, Heidelberg, 2009, pp. 239–247.
- [20] C.-T. Lin, et al., Exploring the brain responses to driving fatigue through simultaneous EEG and fNIRS measurements, *Int. J. Neural Syst.* (2019) 1950018.
- [21] Y. Liu, H. Ayaz, P.A. Shewokis, Mental workload classification with concurrent electroencephalography and functional near-infrared spectroscopy, *Brain-Comput. Interfaces* 4 (3) (2017) 175–185.
- [22] Y. Liu, H. Ayaz, P.A. Shewokis, Multisubject "Learning" for mental workload classification using concurrent EEG, fNIRS, and physiological measures, *Front. Hum. Neurosci.* 11 (2017) 389.
- [23] A. Omurtag, H. Aghajani, H.O. Keles, Decoding human mental states by whole-head EEG+fNIRS during category fluency task performance, *J. Neural Eng.* 14 (6) (2017) 066003.
- [24] S.-K. Yeom, et al., Spatio-temporal dynamics of multimodal EEG-fNIRS signals in the loss and recovery of consciousness under sedation using midazolam and propofol, *PLoS One* 12 (11) (2017) e0187743.
- [25] C.T. Lin, et al., Exploring the brain responses to driving fatigue through simultaneous EEG and fNIRS measurements, *Int. J. Neural Syst.* 30 (1) (2020).
- [26] S.B. Borgheai, et al., Multimodal evaluation of mental workload using a hybrid EEGfNIRS brain-computer interface system, *International IEEE/EMBS Conference on Neural Engineering, NER* (2019).
- [27] A.A. Badarin, V.V. Skazkina, V.V. Grubov, Studying of human's mental state during visual information processing with combined EEG and fNIRS, *Progress in Biomedical Optics and Imaging - Proceedings of SPIE* (2020).
- [28] A.J. Karran, et al., Toward a hybrid passive BCI for the modulation of sustained attention using EEG and fNIRS, *Front. Hum. Neurosci.* 13 (2019).
- [29] T. Nguyen, et al., Utilization of a combined EEG/fNIRS system to predict driver drowsiness, *Sci. Rep.* 7 (2017).
- [30] T. Nguyen, et al., Utilization of a combined EEG/fNIRS system to predict driver drowsiness, *Sci. Rep.* 7 (1) (2017) 1–10.
- [31] L. Trambaiolli, et al., Resting-awake EEG amplitude modulation can predict performance of an fNIRS-based neurofeedback task, in: 2018 IEEE International Conference on Systems, Man, and Cybernetics (SMC), IEEE, 2018.
- [32] A.A. Badarin, V.V. Skazkina, V.V. Grubov, Studying of human's mental state during visual information processing with combined eeg and fnirs, in: Saratov Fall meeting 2019: computations and data analysis: from nanoscale tools to brain functions, *International Society for Optics and Photonics*, 2020.
- [33] M. Balconi, E. Grippa, M.E. Vanutelli, What hemodynamic (fNIRS), electrophysiological (EEG) and autonomic integrated measures can tell us about emotional processing, *Brain Cogn.* 95 (2015) 67–76.
- [34] M. Balconi, M.E. Vanutelli, Competition in the brain. The contribution of EEG and fNIRS modulation and personality effects in social ranking, *Front. Psychol.* 7 (2016).
- [35] M. Balconi, L. Cortesi, D. Crivelli, Motor planning and performance in transitive and intransitive gesture execution and imagination: does EEG (RP) activity predict hemodynamic (fNIRS) response? *Neurosci. Lett.* 648 (2017) 59–65.
- [36] M. Balconi, M.E. Vanutelli, E. Grippa, Resting state and personality component (BIS/BAS) predict the brain activity (EEG and fNIRS measure) in response to emotional cues, *Brain Behav.* 7 (5) (2017) e00686.
- [37] M. Balconi, A. Frezza, M.E. Vanutelli, Emotion regulation in schizophrenia: a pilot clinical intervention as assessed by EEG and optical imaging (Functional near-infrared spectroscopy), *Front. Hum. Neurosci.* 12 (2018) 395.
- [38] D. Rosenbaum, et al., Neuronal correlates of spider phobia in a combined fNIRS-EEG study, *Sci. Rep.* 10 (1) (2020).
- [39] Y. Blokland, et al., Combined EEG-fNIRS decoding of motor attempt and imagery for brain switch control: an offline study in patients with tetraplegia, *IEEE Trans. Neural Syst. Rehabil. Eng.* 22 (2) (2014) 222–229.
- [40] E. Bourel-Ponchel, et al., Non-invasive, multimodal analysis of cortical activity, blood volume and neurovascular coupling in infantile spasms using EEG-fNIRS monitoring, *NeuroImage Clin.* 15 (2017) 359–366.
- [41] A.P. Buccino, H.O. Keles, A. Omurtag, Hybrid EEG-fNIRS asynchronous brain-computer interface for multiple motor tasks, *PLoS One* 11 (1) (2016) e0146610.
- [42] A.M. Chiarelli, et al., Deep learning for hybrid EEG-fNIRS brain-computer interface: application to motor imagery classification, *J. Neural Eng.* 15 (3) (2018) 036028.
- [43] M.J. Khan, K.-S. Hong, Hybrid EEG-fNIRS-Based eight-command decoding for BCI: application to quadcopter control, *Front. Neurobot.* 11 (2017).
- [44] D.J. Leamy, R. Collins, T.E. Ward, Combining fNIRS and EEG to improve motor cortex activity classification during an imagined movement-based task, in: D. D. Schmorrow, C.M. Fidopiastis (Eds.), *Foundations of Augmented Cognition. Directing the Future of Adaptive Systems*, Springer Berlin Heidelberg, Berlin, Heidelberg, 2011, pp. 177–185.
- [45] Z. Wang, et al., BCI monitor enhances electroencephalographic and cerebral hemodynamic activations during motor training, *IEEE Trans. Neural Syst. Rehabil. Eng.* 27 (4) (2019) 780–787.

- [46] X. Yin, et al., A hybrid BCI based on EEG and fNIRS signals improves the performance of decoding motor imagery of both force and speed of hand clenching, *J. Neural Eng.* 12 (3) (2015) 036004.
- [47] C. Zich, et al., Simultaneous EEG-fNIRS reveals how age and feedback affect motor imagery signatures, *Neurobiol. Aging* 49 (2017) 183–197.
- [48] A.R. Anwar, et al., Effective connectivity of cortical sensorimotor networks during finger movement tasks: a simultaneous fNIRS, fMRI, EEG study, *Brain Topogr.* 29 (5) (2016) 645–660.
- [49] G. Zhu, et al., A simplified hybrid EEG-fNIRS brain-computer interface for motor task classification, *International IEEE/EMBS Conference on Neural Engineering, NER* (2017).
- [50] V.V. Grubov, et al., Analysis of real and imaginary motor activity with combined EEG and fNIRS, *Progress in Biomedical Optics and Imaging - Proceedings of SPIE* (2020).
- [51] P. Verma, et al., Performance investigation of brain-computer interfaces that combine EEG and fNIRS for motor imagery tasks, *Conference Proceedings - IEEE International Conference on Systems, Man and Cybernetics* (2019).
- [52] J. Kwon, J. Shin, C.-H. Im, Toward a compact hybrid brain-computer interface (BCI): performance evaluation of multi-class hybrid EEG-fNIRS BCIs with limited number of channels, *PLoS One* 15 (3) (2020) e0230491.
- [53] H. Jeong, et al., Toward comparison of cortical activation with different motor learning methods using event-related design: EEG-fNIRS study, in: 2019 41st Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC), IEEE, 2019.
- [54] L.-C. Chen, et al., Association of concurrent fNIRS and EEG signatures in response to auditory and visual stimuli, *Brain Topogr.* 28 (5) (2015) 710–725.
- [55] S. Dravida, et al., Co-localization of theta-band activity and hemodynamic responses during face perception: simultaneous electroencephalography and functional near-infrared spectroscopy recordings, *Neurophotonics* 6 (04) (2019) 1.
- [56] S. Invitto, et al., Smell and 3D haptic representation: a common pathway to understand brain dynamics in a cross-modal task. A pilot OERP and fNIRS study, *Front. Behav. Neurosci.* 13 (2019) 226.
- [57] F. Putze, et al., Hybrid fNIRS-EEG based classification of auditory and visual perception processes, *Front. Neurosci.* 8 (2014).
- [58] J. Si, et al., Hemispheric differences in electrical and hemodynamic responses during hemifield visual stimulation with graded contrasts, *Biomed. Opt. Express* 8 (4) (2017) 2018.
- [59] C. Zhao, et al., Anticipatory alpha oscillation predicts attentional selection and hemodynamic response, *Hum. Brain Mapp.* (2019) hbm.24619.
- [60] S. Mandal, B.K. Singh, K. Thakur, Classification of working memory loads using hybrid EEG and fNIRS in machine learning paradigm, *Electron. Lett.* 56 (25) (2020) 1386–1389.
- [61] F. Stephan, H. Saalbach, S. Rossi, Inner and overt speech production matures from childhood to adulthood: a combined EEG and fNIRS study, *Psychophysiology* 54 (2017) p. S66-S66.
- [62] A.J. Karran, et al., Toward a hybrid passive BCI for the modulation of sustained attention using EEG and fNIRS, *Front. Hum. Neurosci.* 13 (2019) 393.
- [63] R. Li, et al., Dynamic cortical connectivity alterations associated with Alzheimer's disease: an EEG and fNIRS integration study, *Neuroimage Clin.* 21 (2019) 101622.
- [64] E.E. Rizki, et al., Determination of epileptic focus side in mesial temporal lobe epilepsy using long-term noninvasive fNIRS/EEG monitoring for presurgical evaluation, *Neurophotonics* 2 (2) (2015) 025003.
- [65] S.B. Borgheai, et al., Multimodal exploration of non-motor neural functions in ALS patients using simultaneous EEG-fNIRS recording, *J. Neural Eng.* 16 (6) (2019) 066036.
- [66] A. Güven, et al., Combining functional near-infrared spectroscopy and EEG measurements for the diagnosis of attention-deficit hyperactivity disorder, *Neural Comput. Appl.* 32 (12) (2020) 8367–8380.
- [67] N. Dolu, et al., Effects of methylphenidate treatment in children with ADHD: a multimodal EEG/fNIRS approach, *Psychiatry Clin. Psychopharmacol.* 29 (3) (2019) 285–292.
- [68] R.J. Deligani, et al., Electrical and hemodynamic neural functions in people with ALS: an EEG-fNIRS resting-state study, *IEEE Trans. Neural Syst. Rehabil. Eng.* 28 (12) (2020) 3129–3139.
- [69] E. Gentile, et al., Mutual interaction between motor cortex activation and pain in fibromyalgia: EEG-fNIRS study, *PLoS One* 15 (1) (2020).
- [70] M. Abtahi, et al., Merging fNIRS-EEG brain monitoring and body motion capture to distinguish parkinsons disease, *IEEE Trans. Neural Syst. Rehabil. Eng.* 28 (6) (2020) 1246–1253.
- [71] A. Berger, et al., Brain oscillatory and hemodynamic activity in a bimanual coordination task following transcranial alternating current stimulation (tACS): a combined EEG-fNIRS study, *Front. Behav. Neurosci.* 12 (2018) 67.
- [72] L.-C. Chen, et al., Enhanced visual adaptation in cochlear implant users revealed by concurrent EEG-fNIRS, *NeuroImage* 146 (2017) 600–608.
- [73] J. Choe, et al., Transcranial direct current stimulation modulates neuronal activity and learning in pilot training, *Front. Hum. Neurosci.* 10 (2016).
- [74] M.J. Herrmann, et al., Simultaneous recording of EEG and fNIRS during visuo-spatial and facial expression processing in a dual task paradigm, *Int. J. Psychophysiol.* 109 (2016) 21–28.
- [75] M. Soltanlou, et al., Reduction but no shift in brain activation after arithmetic learning in children: a simultaneous fNIRS-EEG study, *Sci. Rep.* 8 (1) (2018), 1707.
- [76] S. Ludyga, et al., A combined EEG-fNIRS study investigating mechanisms underlying the association between aerobic fitness and inhibitory control in young adults, *Neuroscience* 419 (2019) 23–33.
- [77] D. Safi, et al., Recruitment of the left precentral gyrus in reading epilepsy: a multimodal neuroimaging study, *Epilepsy Behav. Case Rep.* 5 (2016) 19–22.
- [78] A. Machado, et al., Optimal optode montage on electroencephalography/functional near-infrared spectroscopy caps dedicated to study epileptic discharges, *J. Biomed. Opt.* 19 (2) (2014) 026010.
- [79] D.K. Nguyen, et al., Noninvasive continuous functional near-infrared spectroscopy combined with electroencephalography recording of frontal lobe seizures: <i>fNIRS of FLE</i>, *Epilepsia* 54 (2) (2013) 331–340.
- [80] G. Pellegrino, et al., Hemodynamic response to interictal epileptiform discharges addressed by personalized EEG-fNIRS recordings, *Front. Neurosci.* 10 (2016).
- [81] K. Peng, et al., fNIRS-EEG study of focal interictal epileptiform discharges, *Epilepsy Res.* 108 (3) (2014) 491–505.
- [82] K. Peng, et al., Using patient-specific hemodynamic response function in epileptic spike analysis of human epilepsy: a study based on EEG-fNIRS, *NeuroImage* 126 (2016) 239–255.
- [83] P. Pouliot, et al., Hemodynamic changes during posterior epilepsies: an EEG-fNIRS study, *Epilepsy Res.* 108 (5) (2014) 883–890.
- [84] Y. Sun, H. Ayaz, A.N. Akansu, Multimodal affective state assessment using fNIRS + EEG and spontaneous facial expression, *Brain Sci.* 10 (2) (2020).
- [85] P. Vannasing, et al., Potential brain language reorganization in a boy with refractory epilepsy; an fNIRS-EEG and fMRI comparison, *Epilepsy Behav. Case Rep.* 5 (2016) 34–37.
- [86] H. Obrig, et al., Impact of associative word learning on phonotactic processing in 6-month-old infants: a combined EEG and fNIRS study, *Dev. Cogn. Neurosci.* 25 (2017) 185–197.
- [87] D.J. Leamy, T.E. Ward, A novel co-localational and concurrent fNIRS/EEG measurement system: design and initial results, in: 2010 32nd Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC 2010), IEEE, 2010.
- [88] A. Kassab, et al., Multichannel wearable fNIRS-EEG system for long-term clinical monitoring: multichannel Wearable fNIRS-EEG System, *Hum. Brain Mapp.* 39 (1) (2018) 7–23.
- [89] Z. Yuan, X. Lin, Mapping of the brain activation associated with deception using fused EEG and fNIRS, *Progress in Biomedical Optics and Imaging - Proceedings of SPIE* (2019).
- [90] H.O. Keles, R.L. Barbour, A. Omurtag, Hemodynamic correlates of spontaneous neural activity measured by human whole-head resting state EEG + fNIRS, *NeuroImage* 138 (2016) 76–87.
- [91] S. Lee, et al., Dry electrode-based fully isolated EEG/fNIRS hybrid brain-monitoring system, *IEEE Trans. Biomed. Eng.* 66 (4) (2019) 1055–1068.
- [92] D.K. Nguyen, et al., Non-invasive continuous EEG-fNIRS recording of temporal lobe seizures, *Epilepsy Res.* 99 (1–2) (2012) 112–126.
- [93] A. Ishikawa, et al., Development of double density whole brain fNIRS with EEG system for brain machine interface, in: 2011 33rd Annual International Conference of the IEEE Engineering in Medicine and Biology Society, IEEE, 2011.
- [94] S. Fazli, et al., Enhanced performance by a hybrid fNIRS-EEG brain computer interface, *Neuroimage* 59 (1) (2012) 519–529.
- [95] S. Ge, et al., Neural activity and decoding of action observation using combined EEG and fNIRS measurement, *Front. Hum. Neurosci.* 13 (2019) 357.
- [96] H. Ghonchi, et al., Deep recurrent-convolutional neural network for classification of simultaneous EEG-fNIRS signals, *IET Signal Process.* 14 (3) (2020) 142–153.
- [97] A. Saeed, N. Naseer, H. Jabbar, Improving classification performance of hybrid EEG-fNIRS BCI system by channel optimization, *ACM International Conference Proceeding Series* (2020).
- [98] M.J. Khan, U. Ghafoor, K.-S. Hong, Early detection of hemodynamic responses using EEG: a hybrid EEG-fNIRS study, *Front. Hum. Neurosci.* 12 (2018) 479.
- [99] R. Li, et al., Enhancing performance of a hybrid EEG-fNIRS system using channel selection and early temporal features, *Front. Hum. Neurosci.* 11 (2017) 462.
- [100] P. Sirpal, et al., fNIRS improves seizure detection in multimodal EEG-fNIRS recordings, *J. Biomed. Opt.* 24 (05) (2019) 1.
- [101] K.T. Sweeney, et al., Intelligent artifact classification for ambulatory physiological signals, in: 2010 32nd Annual International Conference of the IEEE Engineering in Medicine and Biology Society (EMBC 2010), IEEE, 2010.
- [102] P. Croce, et al., Exploiting neurovascular coupling: a Bayesian sequential Monte Carlo approach applied to simulated EEG fNIRS data, *J. Neural Eng.* 14 (4) (2017) 046029.
- [103] U. Asgher, et al., Enhanced accuracy for multiclass mental workload detection using long short-term memory for brain-computer interface, *Front. Neurosci.* 14 (2020).
- [104] X. Lin, L. Sai, Z. Yuan, Detecting concealed information with fused electroencephalography and functional near-infrared spectroscopy, *Neuroscience* 386 (2018) 284–294.
- [105] A.R. Sereshkeh, et al., Development of a ternary hybrid fNIRS-EEG brain-computer interface based on imagined speech, *Brain-Comput. Interfaces* 6 (4) (2019) 128–140.
- [106] M. Giovannella, et al., Concurrent measurement of cerebral hemodynamics and electroencephalography during transcranial direct current stimulation, *Neurophotonics* 5 (01) (2018) 1.
- [107] J. Si, et al., Correlation between electrical and hemodynamic responses during visual stimulation with graded contrasts, *J. Biomed. Opt.* 21 (9) (2016) 091315.
- [108] Z. Xu, et al., Pilot study on objective evaluation of human auditory ability using hybrid EEG and fNIRS acquisition, 2019 IEEE International Conference on

- Computational Intelligence and Virtual Environments for Measurement Systems and Applications, CIVEMSA 2019 - Proceedings (2019).
- [109] A. Berger, et al., Neural correlates of age-related changes in precise grip force regulation: a combined EEG-fNIRS study, *Front. Aging Neurosci.* 12 (2020).
- [110] S. Ge, et al., Neural activity and decoding of action observation using combined EEG and fNIRS measurement, *Front. Hum. Neurosci.* 13 (2019) 357.
- [111] H. Aghajani, M. Garbey, A. Omurtag, Measuring mental workload with EEG+fNIRS, *Front. Hum. Neurosci.* 11 (2017) 359.
- [112] H. Banville, R. Gupta, T.H. Falk, Mental task evaluation for hybrid NIRS-EEG brain-computer interfaces, *Comput. Intell. Neurosci.* 2017 (2017) 3524208.
- [113] H. Aghajani, A. Omurtag, Assessment of mental workload by EEG+fNIRS, *Conf Proc IEEE Eng Med Biol Soc 2016 (2016) 3773–3776*.
- [114] A. Omurtag, H. Aghajani, H.O. Keles, Decoding human mental states by whole-head EEG+fNIRS during category fluency task performance, *J. Neural Eng.* 14 (6) (2017) 066003.
- [115] N.K. Kasabov, NeuCube: a spiking neural network architecture for mapping, learning and understanding of spatio-temporal brain data, *Neural Netw.* 52 (2014) 62–76.
- [116] T.O. Sharpee, et al., 25th annual computational neuroscience meeting: CNS-2016, *BMC Neurosci.* 17 (Suppl 1) (2016) 54.
- [117] J. Shin, et al., Evaluation of a compact hybrid brain-computer interface system, *Biomed Res. Int.* 2017 (2017) 6820482.
- [118] P.A. Cicalese, et al., An EEG-fNIRS hybridization technique in the four-class classification of alzheimer's disease, *J. Neurosci. Methods* 336 (2020) 108618.
- [119] S.K. Yeom, et al., Spatio-temporal dynamics of multimodal EEG-fNIRS signals in the loss and recovery of consciousness under sedation using midazolam and propofol, *PLoS One* 12 (11) (2017) e0187743.
- [120] R. Rosas-Romero, et al., Prediction of epileptic seizures with convolutional neural networks and functional near-infrared spectroscopy signals, *Comput. Biol. Med.* 111 (2019) 103355.
- [121] A.M. Chiarelli, et al., Deep learning for hybrid EEG-fNIRS brain-computer interface: application to motor imagery classification, *J. Neural Eng.* 15 (3) (2018) 036028.
- [122] J. Hennrich, et al., Investigating deep learning for fNIRS based BCI, *Conf Proc IEEE Eng Med Biol Soc 2015 (2015) 2844–2847*.
- [123] P. Sirpal, et al., fNIRS improves seizure detection in multimodal EEG-fNIRS recordings, *J. Biomed. Opt.* 24 (5) (2019) 1–9.
- [124] H.F. Jeong, F. Gao, Z. Yuan, Machine learning: assessing neurovascular signals in the prefrontal cortex with non-invasive bimodal electro-optical neuroimaging in opiate addiction, *Sci. Rep.* 9 (1) (2019) 18262.
- [125] A. Khalaf, E. Sejdic, M. Akcakaya, A novel motor imagery hybrid brain computer interface using EEG and functional transcranial Doppler ultrasound, *J. Neurosci. Methods* 313 (2019) 44–53.
- [126] A. Khalaf, E. Sejdic, M. Akcakaya, Common spatial pattern and wavelet decomposition for motor imagery EEG- fTCD brain-computer interface, *J. Neurosci. Methods* 320 (2019) 98–106.
- [127] J. Shin, C.H. Im, Performance improvement of near-infrared spectroscopy-based brain-computer interface using regularized linear discriminant analysis ensemble classifier based on bootstrap aggregating, *Front. Neurosci.* 14 (2020) 168.
- [128] L. Hilty, et al., Fatigue-induced increase in intracortical communication between mid/anterior insular and motor cortex during cycling exercise, *Eur. J. Neurosci.* 34 (12) (2011) 2035–2042.
- [129] T.J. Balkin, et al., The process of awakening: a PET study of regional brain activity patterns mediating the re-establishment of alertness and consciousness, *Brain* 125 (10) (2002) 2308–2319.
- [130] G. Zhu, et al., A simplified hybrid EEG-fNIRS brain-computer interface for motor task classification, in: *2017 8th International IEEE/EMBS Conference on Neural Engineering (NER)*, IEEE, 2017.
- [131] C. Zhao, et al., Anticipatory alpha oscillation predicts attentional selection and hemodynamic response, *Hum. Brain Mapp.* 40 (12) (2019) 3606–3619.
- [132] V. Quaresima, M. Ferrari, Functional near-infrared spectroscopy (fNIRS) for assessing cerebral cortex function during human behavior in natural/social situations: a concise review, *Organ. Res. Methods* 22 (1) (2019) 46–68.
- [133] J. Hennrich, et al., Investigating deep learning for fNIRS based BCI, *Annu Int Conf IEEE Eng Med Biol Soc 2015 (2015) 2844–2847*.
- [134] H. Aghajani, A. Omurtag, Assessment of mental workload by EEG+fNIRS, *Annu Int Conf IEEE Eng Med Biol Soc 2016 (2016) 3773–3776*.
- [135] U. Chaudhary, et al., Brain-computer interface-based communication in the completely locked-in state, *PLoS Biol.* 15 (1) (2017) e1002593.
- [136] J. Shin, et al., Improvement of information transfer rates using a hybrid EEG-NIRS brain-computer interface with a short trial length: offline and pseudo-online analyses, *Sensors (Basel)* 18 (6) (2018).
- [137] A. Khalaf, E. Sejdic, M. Akcakaya, Towards optimal visual presentation design for hybrid EEG-fTCD brain-computer interfaces, *J. Neural Eng.* 15 (5) (2018) 056019.
- [138] J. Shin, et al., Simultaneous acquisition of EEG and NIRS during cognitive tasks for an open access dataset, *Sci. Data* 5 (2018) 180003.
- [139] J. Shin, K.R. Müller, H.J. Hwang, Eyes-closed hybrid brain-computer interface employing frontal brain activation, *PLoS One* 13 (5) (2018) e0196359.
- [140] A. von Lüthmann, et al., Toward a wireless open source instrument: functional near-infrared spectroscopy in mobile neuroergonomics and BCI applications, *Front. Hum. Neurosci.* 9 (2015) 617.
- [141] L. Block, et al., Cerebral ischemia detection using artificial intelligence (CIDAD)-A study protocol, *Acta Anaesthesiol. Scand.* (2020).
- [142] V.V. Nikulin, et al., Monochromatic ultra-slow (~0.1 Hz) oscillations in the human electroencephalogram and their relation to hemodynamics, *Neuroimage* 97 (2014) 71–80.
- [143] C. Habermehl, et al., Optimizing the regularization for image reconstruction of cerebral diffuse optical tomography, *J. Biomed. Opt.* 19 (9) (2014) 96006.
- [144] M.I. Banks, et al., Cortical functional connectivity indexes arousal state during sleep and anesthesia, *NeuroImage* 211 (2020) 116627.
- [145] P.H.Rd. Silva, et al., Brain structural-Functional connectivity relationship underlying the information processing speed, *Brain Connect.* 10 (3) (2020) 143–154.